Criterion

FIRE DOOR COMPLIANCE VERIFICATION

Important! This information sheet must be completed in full to obtain certification.

Project
Project Address
Builders Name
Door Numbers
Sales order **(If known)**
OPU/Delivery Of Tags

WALL

- ☐ MASONRY
- ☐ STUD FRAME

STUD MATERIAL
STUD SIZE
WALL SHEETING

DOOR FRAME

- ☐ INSTALLED IN ACCORDANCE WITH FIRE DOOR APPROVAL
- ☐ 51 X 25 REBATE
- ☐ 41 X 25 REBATE

DOOR CLEARANCES

- ☐ TOP & SIDES MAXIMUM 3mm
- ☐ BOTTOM MAXIMUM 15 mm MINIMUM 3 mm

FIRE RATING

- ☐ /60/3 (1HOUR)
- ☐ /120/30 (2HOURS)
- ☐ OTHER (Please Specify)

HARDWARE

MANUFACTURER & MODEL No. MUST BE SPECIFIED!

- ☐ LOCKSET/LATCHSET
- ☐ OTHER
- ☐ LATCHBACKSET
- ☐ DOOR CLOSER
- ☐ CLOSER BACKCHECK

PAIR OF DOORS

- ☐ HEAD LATCH
- ☐ AUTOFLUSH BOLTS
- ☐ SEQUENCE SELECTOR
- ☐ ALUMINIUM MEETING STILES

Important! ONLY TESTED AND APPROVED HARDWARE CAN BE FITTED TO FIRE DOORS.

OPERATION

- ☐ DOOR CLOSED TO FULLY LATCHED POSITION
- ☐ (DOOR MUST LATCH FULLY UNASSISTED).

I the undersigned, declare that the above information is true and correct.
The fire door assembly must comply with as/n7s 1905.1: 2005 before certificate can be issued.

SIGNED DATE ON BEHALF OF

Reset