

## FIRE DOOR COMPLIANCE VERIFICATION

Im	portar	nt! This information sheet mu	ust be comple	eted in full to obtain ce	ertification.	
Project Project address Builders Name Address Contact Phone Door Numbers						
WALL		MASONRY STUD FRAME	STUD MAT STUD SIZE WALL SHE	<u> </u>		
DOOR FRAME		INSTALLED IN ACCORDANCE WITH FIRE DOOR APPROVAL 51 X 25 REBATE 41 X 25 REBATE				
DOOR CLEARANCES		TOP & SIDES MAXIMUM 3mm BOTTOM MAXIMUM 10 mm MINIMUM 3 mm				
FIRE RATING		/60/30 (1 HOUR ) /120/30 (2 HOURS) /180 /30 (3 HOURS) /240/30 (4 HOURS)				
HARDWARE		MANUFACTURER & MODEL No. MUST BE SPECIFIED!				
PAIR OF DOORS		LOCKSET/LATCHSET OTHER LATCHBACKSET DOOR CLOSER CLOSER BACKCHECK	<			
		HEAD LATCH AUTOFLUSH BOLTS SEQUENCE SELECTO ALUMINIUM MEETING				
Important!ONLY T	ESTE	ED AND APPROVED HA	ARDWARE	CAN BE FITTED T	O FIRE DOORS.	
OPERATION		DOOR CLOSED TO FU	JLLY LATCH	IED POSITION	(DOOR MUST LATCH FULLY UNASSISTED)	
I The fire door assembly r	must (	the undersigne comply with as/n7s 1905			nation is true and correct e issued.	
SIGNED		DATE	ON	BEHALF OF		