

COMPANY NAME _____	SUBURB/POSTCODE _____	SITE CONTACT PHONE _____
YOUR NAME _____	ORDER DATE _____	DELIVERY TIME _____
PROJECT NAME _____	DUE DATE _____	SPECIAL INSTRUCTIONS _____
DELIVERY ADDRESS _____	CUSTOMER ORDER # _____	_____
_____	SITE CONTACT NAME _____	_____

DOOR REF #	SIZE					SLIDING TRACK MACHINING (refer to p. 3)	LOCKS & HANDLES				ADDITIONAL MACHINING			
	FINISHED HEIGHT (mm)	FINISHED WIDTH (mm)	THICKNESS (refer to p. 3)	FINISH (refer to p. 3)	EDGE STRIPS		LOCK TYPE (refer to p. 3)	HANDLE TYPE (refer to p. 3)	LOCK HEIGHT (mm to centre of handle)	MACHINE ONLY				
										FACEPLATE		HANDLE HOLES	CYL. HOLE (Outside)	TURN SNIB

SEE NEXT PAGE FOR VISION PANELS

Send completed form to:
VIC orders@criterionindustries.com.au

NSW sales.nsw@criterionindustries.com.au

WA sales.wa@criterionindustries.com.au

TIMBER SLIDING DOOR QUICK ORDER FORM

VISION PANELS

DOOR REF #	VISION PANELS (INSTALLED)					ADDITIONAL MACHINING
	SIZE	SILL HEIGHT (mm)	SIDE MARGIN (mm)	GLAZING (6.38mm or 10.38mm)	GLAZING TYPE (Pocket or beaded glazing)	

SPECIAL INSTRUCTIONS

All hardware must be ordered separately. If provided from a different supplier, please include manufacturer code and specifications for accurate machining.

Send completed form to:
VIC orders@criterionindustries.com.au

NSW sales.nsw@criterionindustries.com.au

WA sales.wa@criterionindustries.com.au

STANDARD MEASURING AND MANUFACTURING DETAILS


Method of measuring	Refer to Product Guide or Website
Standard handle height:	1000mm to centre of handle (unless otherwise specified under Special Instructions)
Standard D-Pull height:	1000mm to centre of handgrip (unless otherwise specified under Special Instructions)
Standard machining details	Cylinder Hole is always machined to outside of door if specified to be machined



SLIDING TRACK OPTIONS

Arctic Sliding Track - Standard	Atlantic Sliding Track
Arctic Sliding Track - Low Clearance	Panama Sliding Track
Tanaro Cavity	Amazon Sliding Track
Acacia Cavity	Artesian Cavity
Niagara Sliding Track	

FINISHING OPTIONS	DOOR THICKNESS	DOOR FINISH	
Description	32mm	MDF - 9mm Skins	Plyface - Semi Solid
	35mm	MDF - 6mm Skins	External Grade - Solid Core
	38mm	MDF - 4.75mm Skins	External Grade - Semi Solid
	39mm - NSW Only	MDF - Solid Core	Duracoat - WA Only
	40mm	MDF - Foam Core	
	44mm	Plyface - Solid Core	

TIMBER SLIDING DOOR MANUFACTURING & MACHINING OPTIONS

LOCK TYPE	SLIDING DOOR 60MM B/SET MORTICE LOCK	NARROW B/SET SLIDING DOOR FLIP LOCK (TONGUE ONLY)
		
Description	Prep for Std Sliding Mortice Lock	Prep for Narrow Backset Sliding Mortice Lock

HANDLE TYPE	FINGER PULL	FLUSH PULL
		
Description	Prep for Finger Pull	Prep for Standard Flush Pull