

RESU16H Prime

16.0kWh Battery Pack Product Specification

RESU 16H Prime

Electrical Characteristics		
Usable Energy ¹⁾		16.0 kWh @77°F (25°C)
Voltage Range	Charge	420 ~ 450 V _{DC}
	Discharge	350 ~ 410V _{DC}
Max. Charge/Discharge Current		20A@350V
Max. Charge/Discharge Power		7 kW
Peak Power (only discharging) ²⁾		11 kW for 10 sec.
Peak Current (only discharging)		32.8A for 10 sec.
Communication Interface		RS485/CAN
DC Disconnect		Circuit Breaker
Connection Method		Spring Type Connector
User interface		LEDs for Normal and Fault operation
Protection Features		Over Voltage / Over Current / short circuit / Reverse Polarity
Scalability (Total Energy, Max. Charge/Discharge Power)		Max. 2 in parallel (32.0 kWh @77°F (25°C), 14kW)

Operating Conditions	
Installation Location	Indoor / Outdoor, Stand only
Operating Temperature	14 ~ 122°F (-10 ~ 50°C)
Operating Temperature (Recommended)	59 ~ 86°F (15 ~ 30°C)
Storage Temperature	-22 to 140°F (-30 to 60°C), acceptable for 7 days in total -4 to 113°F (-20 to 45°C), acceptable for the first 6 months) -4 to 86°F (-20 to 30°C), acceptable for 7th month~12th month
Humidity	5%~95%
Altitude	Max. 6,562ft (2,000m)
Cooling Strategy	Natural Convection

Certification		
Safety	Cell	UL1642
	Battery Pack	UL1973 / CE / RCM / TUV (IEC 62619)
Emissions		FCC
Hazardous Materials Classification		Class 9
Transportation		UN38.3 (UNDOT)
Ingress Rating		IP55

※ Test Conditions - Temperature 77°F (25°C), at the beginning of life

※ Total Energy is measured under specific condition from LGC(0.3CCCV/0.3CC)

※ Product specification may change without notice

1) DOD 100%. DC/DC converter one way efficiency 97.5%. Ambient 77°F (25°C)

2) Peak Current excludes repeated short duration (less than 10 sec. of current pattern).

RESU 16H Prime

Mechanical Characteristics		
Dimensions	Width	19.8 inch (504 mm)
	Height	42.8 inch (1086 mm)
	Depth	11.6 inch (295 mm)
Weight		350 lb (159 kg)



