COREtec Pro Plus

Technical Specifications

Description: Engineered COREtec Pro Plus Floating Floor with Attached Cork Underlayment

Warranty: Lifetime Limited Residential Wear Warranty

Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty

15 Year Limited Commercial Wear Warranty

Installation: Float, Glue Down

Size/Packaging: 7.20" x 48.03" x 5 mm Planks

28.84 sq. ft./carton, 12 planks per carton, 51 lbs. per carton, 50 ctns per pallet

Density: 2000 kg/m3

Pattern Repeat: 5 planks

Construction: 0.5 mm/20 mil wear surface

1.0 mm vinyl base layer

1.5 mm core

1.0 mm vinyl balance layer1.0 mm cork underlayment

Edges/Ends: Micro Bevel

Wear Finish: UV-cured acrylic

Gloss Level: 8% - 10%

TEST DATA

ASTM E492-09 Impact Sound Conduction IIC 57
ASTM E90-09 Airborne Sound Conduction STC 50

ASTM F-970-15 Static Load Limit: 0.02 mm @ 1200 lbs

ASTM F2199 Dimensional Stability: Pass ASTM F1914 Short-Term Indentation: 0.5%

ASTM-E648-15 Critical Radiant Flux: Meets or exceeds, Class 1

ASTM-E662-17 Smoke Density: Pass, Flaming 330

Pass, Non-Flaming 322

Certifications: GREENGUARD GOLD Certified

Environmental Statement: USFloors' commitment is to provide consumers and specifiers with beautiful and durable floors at a

good value, while minimizing our impact on the environment and enhancing and improving it

whenever possible. USFloors is a member of the USGBC.

Country of Origin: Manufactured in China