



Rusty's YJ 1" Body Lift Kit

(YJ) ('87-'95)

Part# [RK-BL100-YJ](#)

Introduction:

Rusty's recommends that this installation be performed by a certified automotive technician or a person with professional mechanical knowledge. Installing this kit without this expertise may jeopardize the handling and safety of the vehicle.

Read instructions several times before starting. Be sure you have all the needed parts and know where they install. Read each step completely as you go. Exhaust modifications may be necessary. You will need an inclinometer or similar tool to check rear driveline angles; this will help take a lot of the guess work out. A front end alignment is a must. Prior to drilling or cutting, check behind the surface being worked on for any wires, lines, or hoses that could be damaged. After any drilling or cutting, remove burrs and grind smooth any surfaces. Be sure to paint or undercoat afterwards.

Before Starting Installation:

1. Carefully Read all warnings and instructions completely before beginning.
2. Verify all parts have been received in this kit by checking the parts list at the beginning of this document.
3. Only install this kit on the vehicle for which it specified.
4. Park the vehicle on a clean, dry, flat, level surface and block the tires so the vehicle cannot roll in either direction.

Parts List:

Please be sure that you have all the provided parts for the kit prior to installing.

<u>Part #</u>	<u>DESCRIPTION:</u>	<u>Quantity</u>
RC-BLP	Rusty's 1" Body Lift Spacer	11
RC-TL1	Rusty's Transmission Linkage Adapter	1
5728415	1/2"-13 x 4-1/2" Length Grade 8 Hex Head Cap Screw	6
5724646	1/2" SAE Flat Washer	6
67522524	7/16"-14 x 3-1/2" Length Grade 8 Hex Head Cap Screw	5
05724638	7/16" SAE Flat Washer	5
05726104	5/16"-18 x 1 Length Grade 8 Hex Head Cap Scew	2
05724612	5/16" SAE Flat Washer	2
67488924	5/16" - 18 Grade 8 Hex Lock Nut	2

Rusty's YJ 1" Body Lift Kit

(YJ) ('87-'95)

Part# [RK-BL100-YJ](#)

Installation

- 1.) Remove the top front splash pan by removing the two M10 bolts on the outside of each frame.
- 2.) Remove the splash pan brace, by removing one bolt from each side on top of the frame rails.
- 3.) Loosen, but do not remove, all 11 body mount bolts. One is located directly in front of the radiator, 6 are located under the doors and between the wheels, and 4 are located in the rear of the vehicle.
- 4.) Position a floor jack under the driver's side of the vehicle with a wooden block on it. Keep doors (if equipped) closed during rising to prevent body flex. Remove the bolts from the front mount, and all 5 mounts on the driver's side. (Keep the stock bushing stacks intact on the vehicle when installing body blocks, unless installing polyurethane body mounts. Install the new body mounts now, then install body block.)
- 5.) Jack up the vehicle high enough (approximately 2 inches) to install spacer blocks between the frame and the body mounts. Be sure to check engine compartment as you are lifting the vehicle for any lines , wires , hoses , or cables which way bind.
- 6.) Install the blocks along the driver's side. Do not install the block in front of the radiator yet. Fasten all bolts loosely, but do not tighten yet.
- 7.) Move floor jack to the passenger side of the vehicle and repeat the installation of the blocks and bolts.
- 8.) With body still raised install the front block at this time.
- 9.) On vehicles equipped with manual trans or automatic transcribe a vertical line along the straight part of the transmission linkage. Scribe a vertical line along the length of the linkage extension provided in the kit.
- 10.) Cut the transmission linkage in half, through the scribed line.
- 11.) Place the linkage extension between the two halves of the transmission linkage, line up all three lines, and weld together. (RUSTY'S recommends that all welding be done by a certified welder)
- 12.) Reinstall the lengthened transmission linkage to the stock mounting positions on the steering column and the transmission.
- 13.) Replace the front splash pan and brace, it may be necessary to notch out approximately 1/2 inch. Tighten all bolts securely.
- 14.) Reinstall the fan shroud, it may be necessary to trim the lower half of the shroud.
- 15.) Check all brake lines to make sure they are not touching or chafing .
- 16.) Check and reattach all other lines, wires, hoses, or cables which may have been loosened or moved for clearance during the raising of the vehicle.
- 17.) Check the shift levers for clearance. On most vehicles no modifications will be necessary, although in some cases you may need to put the transmission into 3rd gear and bend the lever slightly forward toward the dash.
- 18.) Check the steering of the vehicle. Make sure the column rotates fully to the left and right, and that the steering does not bind.
- 19.) Reinstall negative battery cable to battery terminal. Check that all installation steps have been completed. Check all nuts and bolts for tightness.

Rusty's YJ 1" Body Lift Kit

(YJ) ('87-'95)

Part# [RK-BL100-YJ](#)

Final Notes:

Note: Save all factory components and hardware for reuse, unless noted.

At this point there should be no remaining new parts left to be installed except for the stickers.

You need to have the vehicle aligned as soon as possible.

Recommended Alignment Specs:

Castor: +7.0 Degrees

Camber: 0 Degrees

Castor: Starting @ 0 Degrees

Re-torque all fasteners after 500 miles and recheck after 1000 miles. Visually inspect components and re-torque fasteners during routine vehicle service.

WARNING

It is the owners' responsibility to inspect all Rusty's products for proper torque specs to prevent loosening of components. Seat belts and shoulder harnesses should be worn at all times. Re-check all bolts and nuts after the first 300 miles and after any off-road usage during the first 300 miles. Although all of our products are made from the highest quality materials possible, they are not a substitute for Safe and Careful driving. In other words, have good safe on-road / off-road sense. Know the terrain, the speed limitations, and any obstacles that may lie ahead. Please remember to preserve our right to enjoy public land through the proper use of off-road vehicles. Thank you for choosing Rusty's Off Road Products.



For Questions or Suggestions, contact our Tech Department (256-442-0607)