



Max OAL Aporox.
82in/cm

Min OAL Approx.
34in/86cm

Fiddlehead

Cantilever

Series
Fiddlehead

Product
Cantilever

Dimensions
L 99in/252cm x W 10in/25cm x
H 34in/86cm

Weight
10lb/4.5kg

Materials
Steel, glass

Finishes
Blackened steel, oil-rubbed bronze,
brushed brass

Glass Colors
Smoke, clear, cream

Canopy
5-inch round in matching metal finish.

Suspension
1/2" diameter stem in matching metal
finish. 15-inch length included with
lamp. Can be cut down to size on site.

Ceiling Slope
0° mounting slope.
Custom mounting slope available
upon request.

Fixture Mounting
Standard 4in. electrical box. Two #8-32
screws included. Additional mounting
hardware provided for 240V version.

Certifications
UL, cUL (120V)
CE, CB(240V)

LED Bulb Illumination (120V/240V)

Cream Globe
Socket: E26/E27
Bulb: 6 Watt A19 frosted
Wattage: 6 Watts
Lumens: 250 Lumens est.
Color Temperature: 2700K, CRI 90+
Bulb Lifetime: 25,000 hours est.
Dimming: Triac or ELV

Smoke Globe
Socket: E26/E27
Bulb: 3 Watt G25 Clear
Wattage: 3 Watts
Lumens: 210 Lumens est.
Color Temperature: 2700K, CRI 90+
Bulb Lifetime: 25,000 hours est.
Dimming: Triac or ELV

Clear Globe
Socket: E26/E27
Bulb: 3 Watt G25 Clear
Wattage: 3 Watts
Lumens: 600 Lumens est.
Color Temperature: 2700K, CRI 90+
Bulb Lifetime: 25,000 hours est.
Dimming: Triac or ELV