

QuicRun 10BL120 SENSORED G2
QuicRun 10BL120 Sensored
NEW


MODEL	QuicRun 10BL120 SENSORED G2	QuicRun 10BL120 Sensored
Cont. / Peak Current	120A / 760A	120A / 760A
ESC Type	Sensored Brushless	Sensored Brushless
Motor Type	Sensored/Sensorless Brushless motor	Sensored / Sensorless Brushless Motor
Motor Limit	2S Lipo: $\geq 4.5T$ 3S Lipo: $\geq 10.5T$ 3650 size motor	2S Lipo: $\geq 4.5T$ 3S Lipo: $\geq 10.5T$ 3650 size motor
Lipo Cells	2-3S Lipo	2-3S LiPo
BEC Output	6V/7.4V @ 4A (Switch-mode)	6V@3A, Linear Mode
Cooling Fan	Powered by built-in BEC	Powered by the battery
Size / Weight	44(L) x 36.8(W) x 32.3(H) / 101.5g (w/Wires)	43(L) x 36(W) x 33(H)mm (w/ Fan) / 105g (w/ Wires & Fan)
Programming Port	Throttle cable	Throttle cable
Applications	1/10 th Touring Car/Buggy/F1/Drift Car, and etc	1/10 th Touring Car/Buggy/F1/Drift Car, and etc