

**XeRun XR8 PRO G3**

**XeRun XR8 PRO G2**

NEW



MODEL	XeRun XR8 PRO G3	XeRun XR8 PRO G2
Cont. / Peak Current	200A / 1080A	200A / 1080A
ESC Type	Sensored Brushless	Sensorless Brushless
Motor Type	Sensored / Sensorless Brushless Motors	Sensored / Sensorless Brushless Motors
Motor Limit	With 3S Lipo: KV ≤ 4000 3660 Size motor With 4S Lipo: KV ≤ 3000 4268 Size motor	Brushless Motor Limit with 4S LiPo/12S NiMH: 4268/4274 Size Motor, KV ≤ 3000
Lipo Cells	2-4S Lipo	2-4S LiPo
BEC Output	6V/7.4V Adjustable, Continuous Current: 6A	6-8.4V Adjustable, Continuous Current: 6A
Braking mode	FOC/BLDC	BLDC
Fan Type	Frameless fan	Fan with frame
Intelligent fan start/stop	Yes	No
Size / Weight	54.8x36.8x38.8mm/102.8g	56.1x42.1x38.6mm/114g
Programming Port	Multifunction LCD G2 Program Box, OTA Programmer	Multifunction LCD Program Box G2, OTA Programmer
Applications	1/8 Off-road, On-road Racing & 1/10 Short course truck, Monster truck	1/8 Off-Road/On-Road contest