

XeRun V10 G4R

XeRun V10 G4



NEW



Model(Turns)	13.5T	17.5T	13.5T	17.5T	21.5T
KV(No-load)	4100KV	3150KV	3950KV	3020KV	2500KV
LiPos	1-2S	1-2S	2S	2S	2S
Resistance(Ω)	0.0206 Ω	0.0354 Ω	0.021 Ω	0.036 Ω	0.055 Ω
No-load Current	5.4A	4.6A	4.5A	3.7A	3.0A
Rotor	Self-dissipating structure		No Self-dissipating structure		
Current@Max.OutputPower (A)	70.7	49.4	70	51	38
Diameter/Length(mm)	\varnothing =35.8mm(1.41in) L=51.3mm(2.02in)	\varnothing =35.8mm(1.41in) L=51.3mm(2.02in)	\varnothing =35.8mm(1.41in) L=51.4mm(2.024in)	\varnothing =35.8mm(1.41in) L=51.4mm(2.024in)	\varnothing =35.8mm(1.41in) L=51.4mm(2.024in)
Shaft Diameter/Length (mm)	\varnothing =3.175mm(0.125in) L=13.9mm(0.55in)	\varnothing =3.175mm(0.125in) L=13.9mm(0.55in)	\varnothing =3.175mm(0.125in) L=13.9mm (0.547in)	\varnothing =3.175mm(0.125in) L=13.9mm (0.547in)	\varnothing =3.175mm(0.125in) L=13.9mm (0.547in)
Wear-resistant silent gasket	Yes	Yes	No	No	No
Enamelled wire with temperature resistance	220°C	220°C	200°C	200°C	200°C
Poles	2	2	2	2	2
Weight (g)	152g	152g	149g	149g	148g
Applications	1/10 STOCK Racing	1/10 STOCK Racing	1/10 STOCK Racing	1/10 STOCK Racing	1/10 STOCK Racing