

PRODUCT	MODEL	RETICLE	SKU#	PAGE
CRONUS ATS THERMAL SCOPE	50-640	5 MOA RETICLES 5 MIL RETICLES	210132	1/2

IDEAL APPLICATION



PREDATOR
HUNTING



VARMINT
HUNTING

TOP FEATURES

CUTTING-EDGE THERMAL SENSOR

The cutting-edge 12µm pixel thermal sensor offers a high-resolution thermal image and maximum detection range.

HIGH-RESOLUTION OLED DISPLAY

A 0.39" OLED display with a 1440 x 1080 resolution provides a sharp, high contrast view with vivid color.

WIFI & BLUETOOTH


Apple and Android Compatible app allows users to record audio, video, and download images directly to their personal device.

ALL FEATURES


Cutting-edge Thermal Sensor, High-resolution OLED Display, Wifi & Bluetooth, 10 Built-in Interchangeable Reticles, 6 Reticle Color Options, 10 Illumination Settings, 64 GB Memory Capacity, Auto Power-OFF, 6 Color Palette Options, 10 Detection Sensitivity, Auto Shot Record, One Shot Zero, Eco Mode, Waterproof, Fog Proof, Shockproof, Long Battery Life.

RETICLES

MOA RETICLES



MIL RETICLES



SHARP, TIGHT
AND PRICED
JUST RIGHT!

RETICLE COLOR OPTIONS




PRODUCT	MODEL	RETICLE	SKU#	PAGE
CRONUS ATS THERMAL SCOPE	50-640	5 MOA RETICLES 5 MIL RETICLES	210132	2/2

THERMAL SENSOR	640 x 480 @12µm			
NETD	≤25mK @ 77°F/25°C			
DISPLAY RESOLUTION	1440 x 1080			
DISPLAY	0.39" OLED			
LENS SYSTEM	50 mm F1.0			
FIELD OF VIEW	8.8° x 6.6°			
BASE MAGNIFICATION	2.36X			
COMBINED MAGNIFICATION	18.9X			
EYE RELIEF	1.9"			
DETECTION RANGE	3600 Yds			
RECOGNITION RANGE	2190 Yds			
COLOR PALETTES	White Hot, Black Hot, Adjustable Red Hot, Green Hot, Iron Red, Blue Hot			
RETICLE	10 Built-in Reticles (5 MOA, 5 MIL)			
RETICLE ADJUSTMENT	Digital			
DISTANCE MEASUREMENT	Stadiametric Ranging			
VIDEO RECORD / SNAPSHOT	1440 x 1080			
BUILT-IN MEMORY	64 GB			
WI-FI CONNECTION	Yes			
STANDBY MODE	Yes			
BATTERY	1 Built-in Battery, and 2 Spare External Batteries			
BATTERY LIFE	≥ 10 h @ 77°F/25°C			
EXTERNAL POWER	5V2A Adapter (USB Type-C)			
WORKING TEMPERATURE	-22°F to 122°F / -30°C to 50°C			
WATERPROOF	IP67			
WEIGHT	35.3 oz			
ZEROING PROFILES	10			

DETAILED DIMENSIONS

L1	L2	L3	L4	L5	L6	D1	D2
14.7"	4.9"	5.6"	4.2"	1.9"	1.9"	1.75"	2.35"



**SHARP, TIGHT
AND PRICED
JUST RIGHT!**