

PRODUCT	MODEL	RETICLE	SKU#
HELOS BTR GEN2 RIFLESCOPE	6-24x56 FFP	APLR6 FFP IR MOA	214113

IDEAL APPLICATION



ALTERNATIVE APPLICATION



TOP FEATURES

ADVANCED FULLY MULTI-COATED

Athlon advanced fully multi-coated glass gives you better light transmission with optimum brightness and true color across the entire light spectrum.

PRECISION ZERO STOP

Our precision zero stop system allows you to return to your initial zero position with a sharp and precise stop, right on your initial zero.

LOCKING TURRETS

Athlon Optic's locking turrets allow you to pull up on your turret to dial and push down on the turret to lock it in place to avoid inadvertent adjustments.

ALL FEATURES


- ADVANCED FULLY MULTI-COATED LENSES
- XPL PROTECTIVE COATING
- ARGON PURGED
- PRECISION ZERO STOP
- LOCKING TURRETS
- HIGH PRECISION ERECTOR SYSTEM
- AIRCRAFT GRADE ALUMINUM TUBE
- ILLUMINATED RETICLE
- ETCHED GLASS RETICLE
- WATERPROOF
- FOG PROOF
- SHOCKPROOF
- ONE PIECE TUBE CONSTRUCTION

SPECS

Power	6-24X
Obj. Lens	56 mm
Tube Size	34 mm
Turrets	Exposed / Locking
Eye Relief	3.7"
FoV @100Y	19.9-5.12 ft
Click Value	0.25 MOA
Adjustment Per Rotation	25 MOA
Total Elevation Adjustment	100 MOA
Total Windage Adjustment	80 MOA
Parallax Adjustment	Side Focus 10yds-∞
Purging Material	Argon
Weight	34.5 oz

DIMENSIONS

L1	L2	L3	L4	L5	L6	D1	D2
14.3"	4.75"	6.0"	3.55"	2.4"	2.0"	1.85"	2.5"



**SHARP, TIGHT
AND PRICED
JUST RIGHT!**