

PRODUCT	MODEL	RETICLE	SKU#
TALOS RIFLESCOPE	6-24x50 SFP	BDC 600 SFP IR	215012

IDEAL APPLICATION



TOP FEATURES

NITROGEN PURGED

Paired with a completely sealed chassis, nitrogen gas is used to purge air from the optic to help maintain internal fog-proof and waterproof capabilities.

FULLY MULTI-COATED

Athlon Optic's fully multi-coated glass gives you better light transmission with optimum brightness and true color across the entire light spectrum.

WATERPROOF

Regardless of how heavy the rain is coming down or an accidental drop in the water, this sealed and gas-purged optic will remain waterproof.

ALL FEATURES


- FULLY MULTI-COATED LENSES
- NITROGEN PURGED
- AIRCRAFT GRADE ALUMINUM TUBE
- ILLUMINATED RETICLE
- ETCHED GLASS RETICLE
- WATERPROOF
- FOG PROOF
- SHOCKPROOF
- ONE PIECE TUBE CONSTRUCTION

SPECS

Power	6-24X
Obj. Lens	50 mm
Tube Size	1 mm
Turrets	Capped
Eye Relief	3.03-3.11"
FoV @100Y	16.8-4.5 ft
Click Value	0.25 MOA
Adjustment Per Rotation	15 MOA
Total Elevation Adjustment	60 MOA
Total Windage Adjustment	60 MOA
Parallax Adjustment	Side Focus 10yds-∞
Purging Material	Nitrogen
Weight	23 oz

DIMENSIONS

L1	L2	L3	L4	L5	L6	D1	D2
13.9"	4.0"	6.2"	3.7"	1.9"	2.7"	1.8"	2.2"



**SHARP, TIGHT
AND PRICED
JUST RIGHT!**