# **Thermal Laminator**



The versatile 45" and 65" thermal laminators enables users to encapsulate, laminate and mount with ease.



### **Highlights**

- Quality Silicon Rollers Providing consistent heat distribution across nip
- Independent Heaters Program up to 9 settings for top and bottom roller temperature
- Release Liner Take-up Included as a standard option for cold and heat assist lamination
- Convenient Features Digital controls, quick notch gap adjustment, rear remote and rear cross cutter
- Operator Protection Safety shield designed to keep operators hands away from the hot rollers

## **Thermal Laminator**



**HOT & COLD LAMINATION** 

**SPEEDS UP TO** 13 FT./MIN.

CONVENIENT **FEATURES** 



	$\sim$ 11		ITC
ш	ισн	1 1 5	HTS
_			

**Maximum Width** RSH-1651 **RSH-1151 Maximum Speed** Cold Hot Maximum Temperature Mounting **Gap Adjustment** 

Rewinder Reverse Table

**Front Feeder** 

**Emergency Stops Rear Remote Shaft Size** 

13 ft./min. (8.5 m./min.) 9.8 ft./min. (8.5 m./min.)

65" (1650 mm)

45" (1150 mm

320°F (160°C) Up to 5/8" **Quick Notch** 

Optional (RSH-1651) Optional (RSH-1651)

Removable Front & Rear Facing

> Yes 3" Auto-Grips

### **DIMENSIONS & WEIGHT**

Dimensions (WxDxH) **RSH-1651 RSH-1151** 

Weight **RSH-1651** 

**RSH-1151** 

**Crate Dimensions** (WxDxH) **RSH-1651** 

**RSH-1151 Crate Weight RSH-1651** 

**RSH-1151 UPC Code RSH-1651** 

**RSH-1151** 

77" x 36" x 48" 59" x 36" x 48"

593 lbs.

373 lbs.

86" x 36" x 58" 66" x 36" x 58"

869 lbs. 617 lbs.

8 49023 07014 6 8 49023 07013 9

**Warranty** Parts & Labor 1 Year

Yes