

## Specifications

<b>Camera</b>	
<b>Image Sensor</b>	5MP CMOS Image Sensor
<b>Video Resolution</b>	2560 (H) × 1944 (V)
<b>Signal System</b>	PAL/NTSC
<b>Frame Rate</b>	PAL: 5MP@20 fps, 4MP@25 fps, 1080p@25 fps
<b>NTSC: 5MP@20 fps, 4MP@30 fps, 1080p@30 fps</b>	
<b>Lens</b>	2.7—13.5 mm Motorized Varifocal Lens
<b>Min. Illumination</b>	Color: 0.01 Lux @ (F1.2, AGC On), 0 Lux with IR
<b>Horizontal Field of View</b>	95.7° — 29.1°
<b>Number of Infrared LEDs</b>	4
<b>Night Vision Distance</b>	Up to 130 ft/40 m
<b>DNR</b>	2D DNR
<b>Wide Dynamic Range</b>	Digital WDR
<b>OSD Menu</b>	Support
<b>Day &amp; Night</b>	IR-Cut Filter
<b>Video Output</b>	HD BNC X1
<b>Switch Button</b>	TVI/AHD/CVI/CVBS
<b>Housing</b>	Front Cover: Metal, Main Body: Plastic
<b>Color</b>	White
<b>Operating Power</b>	DC 12 V
<b>Operating Temperature</b>	-40 °F — 140 °F / -40 °C — 60 °C
<b>Indoor/Outdoor</b>	Indoor/Outdoor
<b>Weatherproof Rating</b>	IP67
<b>Dimension (L x W x H)</b>	84.5 mm × 92 mm × 255.1 mm (3.33" × 3.62" × 10")
<b>Weight</b>	Approx. 665 g (1.47 lbs.)