

		Key features
		<p>High quality imaging with 4K, 3840×2160 resolution</p> <p>2.8 mm fixed focal lens</p> <p>Up to 25 m IR distance for bright night imaging</p> <p>Up to 20 m white light distance for bright night imaging</p> <p>One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Water and dust resistant (IP67)</p>
Model Number		CS1EQ
Analog HD Camera		
Camera	Image sensor	4K CMOS Image sensor
	Video Resolution	3840 (H) × 2160 (V)
	Signal System	PAL/NTSC
	Frame Rate	<p>TVI: 8MP @12.5 fps, 8MP @15 fps, 4MP @25 fps, 4MP @30fps, 2MP @25 fps, 2MP @30 fps</p> <p>AHD: 8MP@15fps</p> <p>CVI: 8MP@12.5fps, 8MP@15fps</p> <p>CVBS: PAL/NTSC</p>
	Lens	2.8mm
	Min.Illumination	Color:0.01 Lux @ (F1.6,AGC ON),0 Lux with IR
	Angle of View	2.8 mm, horizontal FOV: 108°, vertical FOV: 59°, diagonal FOV: 127°
	Supplement Light type	White Light,IR
	Supplement Light Range	IR : Up to 25 m, white Light : Up to 20 m
	Supplement Light Mode	IR light works normally, and it switches to white light when human or vehicle are detected at night.
	Wide Dynamic Range	Digital WDR
	Audio	/
	IR Cut Filter	Yes
Video Output	BNC, switchable TVI/AHD/CVI/CVBS	
General	Housing	Plastic
	Color	White
	Operating Power	DC12V
	Operating Temperature	-40 °F – 140 °F /-40 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L x W x H)	138.8 mm × Ø70 mm (5.46" × Ø2.76")
	Weight	Approx. 160 g (0.35 lb.)
Packaging Contents		
Camera		1
BNC Cable		/
Power Adapter		/
Mounting Screws Bag		1
User's Manual For Camera		1

		Key features
		High quality imaging with 4K, 3840×2160 resolution 2.8 mm fixed focal lens Up to 25 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)
Model Number		CS1ES
Analog HD Camera		
Camera	Image sensor	4K CMOS Image sensor
	Video Resolution	3840 (H) × 2160 (V)
	Signal System	PAL/NTSC
	Frame Rate	TVI: 8 MP @12.5 fps, 8 MP @15 fps, 4 MP @25 fps, 4 MP @30fps, 2 MP @25 fps, 2 MP @30 fps AHD: 8MP@15fps CVI: 8MP@12.5fps, 8MP@15fps CVBS: PAL/NTSC
	Lens	2.8mm
	Min.Illumination	Color:0.01 Lux @ (F1.6,AGC ON),0 Lux with IR
	Angle of View	2.8 mm, horizontal FOV: 108°, vertical FOV: 59°, diagonal FOV: 127°
	Supplement Light type	White Light & IR
	Supplement Light Range	IR : Up to 25 m, white Light : Up to 20 m
	Supplement Light Mode	IR light works normally, and it switches to white light when human or vehicle are detected at night.
	Wide Dynamic Range	Digital WDR
	Audio	/
	IR Cut Filter	Yes
	Video Output	BNC, switchable TVI/AHD/CVI/CVBS
General	Housing	Plastic & Metal
	Color	White
	Operating Power	DC12V
	Operating Temperature	-40 °F – 140 °F /-40 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L x W x H)	84.6 mm × Ø 85.02 mm (3.33" × Ø 3.35")
	Weight	Approx. 230 g (0.51 lb.)
Packaging Contents		
Camera	1	
BNC Cable	/	
Power Adapter	/	
Mounting Screws Bag	1	
User's Manual For Camera	1	