

AC800 Bullet Camera (Model Number: I91BY)		
Camera	Image Sensor	1/1.8" Progressive Scan CMOS
	Video Resolution	50 Hz: 25 fps (3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 24 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
	Sub Stream	50 Hz: 25 fps (640 × 480, 640 × 360) 60 Hz: 30 fps (640 × 480, 640 × 360)
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps ~ 16 Mbps
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
	Audio Input/Output	1X Built-in Microphone; 1X built-in Speaker
	Environment Noise Filtering	Yes
	Lens	2.8 mm
	Min. Illumination	0.003 Lux@(F2.0, AGC On)
	Angle of View	Horizontal FOV: 110°, Vertical FOV: 57°, Diagonal FOV: 134°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	120 dB WDR
	Network Storage	Local Storage & NAS (NFS, SMB/CIFS)
	ONVIF	Support
	Day/Night Switch	Day, Night, Auto, Schedule
	Ethernet	RJ45 X1 (10 M/100 M)
General	Housing	Plastic & Metal
	Color	White
	Operating Power	PoE (802.3af), 12 V DC ± 25%
	Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB
	Hardware Reset	Yes
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	72.9 mm X 73.3 mm X 191.1 mm (2.9" X 2.9" X 7.5")
	Weight	Approx. 595 g (1.3 lbs.)
AC800 Bullet Camera (Model Number: I91BY)		
Camera	Image Sensor	1/1.8" Progressive Scan CMOS
	Video Resolution	50 Hz: 25 fps (3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 24 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
	Sub Stream	50 Hz: 25 fps (640 × 480, 640 × 360) 60 Hz: 30 fps (640 × 480, 640 × 360)
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps ~ 16 Mbps
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
	Audio Input/Output	1X Built-in Microphone; 1X Built-in Speaker
	Environment Noise Filtering	Yes
	Lens	2.8 mm
	Min. Illumination	0.003 Lux@(F2.0, AGC On)
	Angle of View	Horizontal FOV: 111°; Vertical FOV: 59°; Diagonal FOV; 134°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	120 dB WDR
	Network Storage	Local Storage & NAS (NFS, SMB/CIFS)
	ONVIF	Support
	Day/Night Switch	Day, Night, Auto, Schedule
	Ethernet	RJ45 X1 (10 M/100 M)
General	Housing	Plastic & Metal
	Color	White
	Operating Power	PoE (802.3af), 12 V DC ± 25%
	Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB
	Hardware Reset	Yes
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	∅ 138.3 mm X 124.5 mm (∅ 5.4" X 4.9")
	Weight	Approx. 840 g (1.9 lbs.)