BSP002	Amount	*Adopts 8-mic array, picking up 360° clear sound with 5 meters range  *Adopts the HD speaker  *Supports steady and transient smart noise reduction, echo and squeal suppression, anti-reverberation to enhance speech quality and offer audio in high quality  *The built-in 7.2 V/3700 mAh lithium battery supports the device to last 10 hours after a full charge.  *Supports wireless connection through Bluetooth and a USB dongle  *Supports wired connection through a USB cable  *Driver-free design enables plug-and-play  *Compatible with leading online conferencing platform  8 mic omnidirectional array
Microphone	Туре	360° Omni-directional
	Pickup Distance	Up to 5 m
	Sensitivity	-38 dBV/Pa
	SNR	65 dB
	Frequency Response	100 Hz to 8 kHz
	Sampling Rate	16 kHz/32 kHz/48 kHz
	Special Function/Algorithm	Beam forming
	3A Algorithm	AEC, ANS, AGC
Speaker	Rated Power	3 W
	Speaker Range	In the radius up to 8 m
	Maximum Output Loudness	81 dBSPL @1 m, 1 kHz
	Total Harmonic Distortion	<1% @ 1 kHz
	Effective Bandwidth (-10 dB)	150 Hz to 15 kHz
Functions	Audio Function	Supports steady noise reduction, such as the sound of air conditioner and fan, andtransient noise reduction, such as the sound of falling, claps and steps. Supports echo and squeal suppression, anti-reverberation to enhance speech qualityand offer audio in high quality.
	LED Indicator	Ambient light: Solid White: picking up sounds. Solid Red: mute. Green Light: speaker volume  Bluetooth light Solid White: Only previously paired devices can connect to Bluetooth. Flashing Blue: Unpaired devices can be paired with Bluetooth. Solid Blue: The speakerphone connects to Bluetooth successfully Light remains off: Bluetooth is off.  Power light Charging status: flashing white: charging; solid white: charging completed Non-charging status: solid red: battery ≤ 15%; solid yellow: 15% < battery ≤ 30%; solid white: battery > 30%
Communication	Communication Method	Bluetooth, USB Dongle, USB cable
	Wireless Communication Distance	10 m
	Wired Communication Distance	Cable length: 2 m
Battery	Capacity	7.2 V/3800 mAh
	Battery Life	10 hours when the volume is turned on to 75%. The actual battery life depends on the usage environment and the battery health.
	Quick Charge Protocol	PD 3.0 Protocol
	Charging Temperature	0 ℃~45 ℃
Interface	Cable	Cable in package: type-C-to-C interface (with a type-C-to-A adapter on the cable)
	Device Interface	USB Type C interface
General	Power	5 VDC ± 5%, max. 4.8 W
	Operating Condition	-10 °C to 45 °C (14 °F to 113 °F). Humidity 90% or less (non-condensing)
	System Requirement	Windows XP/7/8/10/11
		Android 8.1 and above version
		Linux 4.14 and above version
		macOS 10.12 and above version
	Dimension	142.2 mm × 93.9 mm × 69.2 mm (5.60" × 3.70" × 2.72")
	Package Dimension	273 mm × 140 mm × 82 mm (10.75" × 5.51" × 3.23")
	Weight	Approx. 645 g (1.42 lb.)
	With Package Weight	Approx. 1190 g (2.62 lb.)
	Color	Silver gray
Accessory	Packing List	Speakerphone × 1
		USB 3.0 cable (2 m) × 1
		USB Dongle × 1
		Quick Start Guide × 1
		Storage case box × 1