

ANNKE C800 Bullet PoE Security Camera Specifications (Model Number: I91BD)		
Camera	Image Sensor	1/2.5" Sony Progressive Scan CMOS
	Video Resolution	8MP (3840 X 2160@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps - 16 Mbps
	Lens	2.8 mm
	Min. Illumination	0.01 Lux @(F1.2, AGC On)
	Angle of View	102°
	Number of Infrared LEDs	2 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
General	Ethernet	RJ45 X1 (10 M/100 M)
	Housing	Metal
	Color	White
	Operating Power	PoE (802.3af)
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension	6.1" X 2.8"/155 X 70 mm
	Weight	0.9 lb./410 g
ANNKE C800 Turret PoE Security Camera Specifications (Model Number: I91BF)		
Camera	Image Sensor	1/2.5" Sony Progressive Scan CMOS
	Video Resolution	8MP (3840 X 2160)
	Signal System	PAL/NTSC
	Video Compression	H.265+/H.265/H.264+/H.264
	Video Bitrate	32 Kbps - 16 Mbps
	Lens	2.8 mm
	Min. Illumination	0.01 Lux @(F1.2, AGC On)
	Angle of View	Diagonal FoV: 124°
	Number of Infrared LEDs	1 pc
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	120 dB True WDR
	ONVIF	Support
	IR-Cut Filter	Yes
General	Ethernet	RJ45 X1 (10 M/100 M)
	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 128 GB
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension	5" X 3.8"/127.3 X 95.9 mm
	Weight	1.4 lbs./620 g
ANNKE C800 Dome PoE Security Camera Specifications (Model Number: I91BE)		
Camera	Image Sensor	1/2.5" Sony Progressive Scan CMOS
	Video Resolution	8MP (3840 X 2160@15 fps)
	Signal System	PAL/NTSC
	Video Compression	H.265/H.264
	Video Bitrate	32 Kbps - 16 Mbps
	Lens	4 mm
	Min. Illumination	0.01 Lux @ (F1.2, AGC On)
	Angle of View	79°
	Number of Infrared LEDs	3 pcs
	Night Vision Distance	Up to 100 ft/30 m
	DNR	3D DNR
	Wide Dynamic Range	Digital WDR
	ONVIF	Support
	IR-Cut Filter	Yes
General	Ethernet	RJ45 X1 (10 M/100 M)
	Housing	Metal & Plastic
	Color	White
	Operating Power	DC 12 V; PoE (802.3af)
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Vandal-Proof Rating	IK10
	Dimension	4.4" X 3.2"/111 X 82.4 mm
	Weight	1.1 lbs./500 g