

		<ul style="list-style-type: none"> · Up to 3K/5MP Lite high definition live viewing · Up to 3K Lite/5MP/5MP Lite recording & playback · Built-in 1024 GB eSSD, 2 weeks continuous recording for 8 channle camera · Deep learning-based motion detection 2.0 for all analog channels · Advanced H.265 Video Compression · Aduio via coaxial cable · Support TVI/AHD/CVI/CVBS/IPC input. 5 in 1 · Supports iPhone、iPad、Android mobile remote monitoring 	
Model Number		DT81BH	
DVR			
Video & Audio	Video Compression	H.265 Pro/H.265/Scene-Adaptive Bitrate Control coding	
	Video Input	8CH Analog HD/Analog + 2CH IP (each up to 5 Mbps)	
	Video Output	HDMI/VGA up to 1080p/60 Hz	
	Audio Input/Output	8-ch via coaxial cable/1-ch via HDMI	
	Supported Camera Types	1)TVI Input: 3K@20fps,5 MP@20 fps, 4MP@30/25fps,,1080p@30/25 fps, 720p@60/50/30/25 fps;	
		2)AHD Input: 5 MP@20 fps, 4MP@30/25fps,,1080p@30/25 fps, 720p@30/25 fps;	
		3)CVI Input: 5 MP@20 fps, 4MP@30/25fps,,1080p@30/25 fps, 720p@30/25 fps;	
		4)CVBS: Support	
	Analog HD Playback Resolution	Main stream: When 1080p Lite mode not enabled: For 5 MP stream access: 5 MP Lite@12 fps; 4 MP Lite/1080p@15 fps; 720p/WD1/4CIF/VGA/CIF@20 fps For 1080p stream access: 1080p/720p@15 fps; WD1/4CIF@25 fps (P)/30 fps (N) For 720p stream access: 720p/WD1/4CIF@25 fps (P)/30 fps (N) When 1080p Lite mode enabled: 5 MP/3K Lite@12 fps; 4 MP Lite/@15 fps; 1080p Lite/720p/WD1/4CIF@25 fps (P)/30fps (N)	
	IP Camera Input	2-CH	
IPC Recording Resolution	Up to 6MP		
IPC Playback Resolution	Up to 6MP		
Max Playback Channel	4CH		
Motion Detection 2.0(Human/Vehicle Analysis)	Up to 8CH: Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights		
ONVIF	Support		
Network	Total Bandwidth	96 Mbps. Incoming bandwidth: 8 Mbps	
	Remote Connection	64	
	Network Protocol	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, UPnP™, HTTPS	
	Network Interface	1, RJ45 10/100 Mbps self-adaptive Ethernet interface	
Hard Drive	SSD	Build in SSD	
	SSD Capacity	Built-in 1024 GB eSSD (960 GB available) Note: The device can store about 2 weeks videos for 8-ch analog cameras (default parameters),this estimation is for reference only.	
Auxiliary Interface	USB	USB 2.0 X2	
General	Working Temperature	14 °F - 113 °F/-10 °C - 45 °C	
	Dimensions (W x D x H)	172 X 121.6 X 46 mm (6.7x4.79x1.81inch)	
	Weight	≤0.5Kg (With eSSD,1.1lb.)	
	Operating Power	DC12V, 1A, ≤ 8.2 W (With eSSD)	
Packaging Contents			
DVR		1	
USB Mouse		1	
Power Adapter		1	
HDMI Cable		1	
Network Cable		1	
User's Manual For DVR		1	