

		<p>Key features</p> <ul style="list-style-type: none"> ◆ 2-megapixel high resolution (1920X1080) for clear picture quality ◆ Clear and smooth video browsing; intelligent transmission giving full play to capabilities of the network ◆ Online firmware upgrade, and synchronous updating of the functions and experience ◆ Two-way voice intercom supported; echo eliminated; noise suppressed ◆ Compatible with Android; remote real-time monitoring supported with the IOS intelligent terminal ◆ Lighting for infrared night vision (with a night vision distance of 7m); 24h around-the-clock monitoring; IR-CUT switching; free of color cast in the daytime; clearer night vision ◆ The built-in rechargeable lithium battery with long battery life functions for up to 6 months under normal circumstances and can stand by for 12 months ◆ 2.4G Wi-Fi supported (IEEE802.11b/g/n) ◆ Cloud storage, Micro SD card (up to 128GB) and mobile phone video recording supported ◆ QR code intelligent connection and network allocation supported ◆ Supporting human contour detection, activity zone, intelligent push and pet snapshot, Package inspection (value added service required) ◆ IP65 Easy installation
Model Number		I41DC
Camera	Sensor	1/2.9" CMOS
	Focal Length	3.0mm
	Aperture	F2.0
	Optical Field of View	125° diagonal, 106° horizontal, 57° vertical
	Minimum Illumination	0.01 lux
Audio	Input	Built-in microphone
	Output	Built-in speaker
	Two-way Audio	Full duplex
	Audio Compressing	AAC
Video	Video Compressing	H.264
	Lighting Frequency	50 Hz, 60 Hz
	Frame Rate	15 fps
	Maximum Resolution	1920 x 1080
	Light Source For Night Vision	White light or infrared LED or Starlight optional
Network	Wireless Standard	2.4 GHz Wi-Fi (IEEE 802.11 b/g/n)
	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUDP
	IP Address Type	Dynamic IP address
Recording	Recording Method	Alarm triggered recording, and manual recording
	Video Storage	Cloud storage, local Micro SD card (up to 128 GB), and mobile phone memory
Function	AI Function	Human contour detection, activity zone, intelligent push, pet snapshot, package inspection
	Wake-up Method	PIR body induction wake-up and remote wake-up
	Alarm Notification	Alarm push by mobile app and alarm sound warning
	Indicator	RGB tri-color LED
Battery	Capacity	5200mAh or 6700mAh Optional
	Removability	Unremovable
	Working Time	6 months (recording 20 pieces of 10-second video per day)
	Standby Time	1 year
	Charging Voltage	5 V ±5%
	Charing Current	1.5 A
	Charging Time	Within 10 hours
	Protection	Over-charge, over-discharge, over-current, short circuit and charging protection at high and low temperature
Power Consumption	Standby	1.68 mW
	Daytime Working	0.88 W
	Nighttime Working	2.20 W
Interface	Power	TYPE-C USB
	Storage	Micro SD card
	Key	Power key and reset key
Installation	Installation Method	Wall mount, desktop
	Bracket Type	Magnet and 1/4" universal screw holes
Environment	Dustproof and Waterproof	IP65
	Charging Temperature	0 °C ~ 45 °C
	Operating Temperature	-10 °C ~ 45 °C
	Storage Temperature	-20 °C ~ 60 °C
Product Dimension	Dimension	67 mm × 58 mm × 89 mm (without bracket)
	Material	ABS + PC
	Color	White

Packaging Contents

Bird Feeder Cam	1	
Black Strap	1	
Roof	1	
Mounting Screws	1	
Anchors	1	
Perch Screw	1	
Perch	1	
Bird Feeder Cam	1	
Hose Clip	4	
Ejector Pin	1	
Type C Power Cable	1	
Mounting Bracket	1	
Antenna	1	
fruit fork	2	
Quick Guide (Bird Feeder Cam)	1	
Solar Panels	1	
Solar Panels Bracket	1	
Quick Guide (Solar Panels)	1	