



### Key features

- 100% Wire-Free
- 3MP Full HD video quality, live stream, and watch recordings
- AI Human detection
- 9000mAh rechargeable battery
- Support Dual light design
- PIR Motion Sensor, Instant&Accurate Alerts
- Support Human detection
- Support two-way audio
- Support up to 128G TF card to store
- Support cloud storage
- Support Amazon Alexa
- Support Android /iOS system mobile devices, remote real-time monitoring
- IP65 Dust and Waterproof Rating

<b>Model Number</b>		<b>I71GN</b>
<b>Warranty</b>		<b>1 Year</b>
<b>Camera</b>	Sensor	1/2.9" CMOS
	Focal Length	3.2 mm
	Aperture	F2.2
	Optical Field of View	128° diagonal, 96° horizontal, 56° vertical
	Minimum Illumination	0.01 lux
<b>Audio</b>	Input	Built-in microphone
	Output	Built-in speaker
	Two-way Audio	Full duplex
	Audio Compressing	AAC
<b>Video</b>	Video Compressing	H.264, H.265
	Lighting Frequency	50 Hz, 60 Hz
	Frame Rate	15 fps
	Maximum Resolution	3MP (2048*1536)
	Light Source For Night Vision	White light or infrared LED switchable
<b>Network</b>	Wireless Standard	2.4 GHz Wi-Fi (IEEE 802.11 b/g/n)
	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUDP
	IP Address Type	Dynamic IP address
<b>Recording</b>	Recording Method	Alarm triggered recording, and manual recording
	Video Storage	Cloud storage, local Micro SD card (up to 128 GB), and mobile phone memory
<b>Function</b>	AI Function	Human detection, vehicle detection, pet detection, package detection, activity zone
	Wake-up Method	PIR body induction wake-up and remote wake-up
	Alarm Notification	Alarm push by mobile app, white LED flashing and alarm sound warning
	Rotation Angle	355° pan, 90° tilt
	Indicator	RGB tri-color LED
<b>Battery</b>	Capacity	9000 mAh
	Removability	Unremovable
	Working Time	8 months (recording 20 pieces of 10-second video per day; pan & tilt unused)
	Standby Time	2 years
	Charging Voltage	5 V ±5%
	Charing Current	1.5 A
	Charging Time	15 hours
<b>Power Consumption</b>	Protection	Over-charge, over-discharge, over-current, short circuit and charging protection at high and low temperature
	Standby	1.68 mW
	Daytime Working	0.88 W
<b>Interface</b>	Nighttime Working	2.23 W
	Power	Micro USB
	Storage	Micro SD card
<b>Installation</b>	Key	Power key and reset key
	Installation Method	Wall mount, ceiling mount, desktop
	Bracket Type	1/4" universal screw hole
<b>Environment</b>	Dustproof and Waterproof	IP65
	Operating Temperature	-10 °C ~ 45 °C
	Storage Temperature	-20 °C ~ 60 °C
<b>Product Dimension</b>	Dimension	140(L)mm x 123(W)mm x 133mm(H) (without bracket)
	Bare Weight	700 g
	Finished Weight	800 g
	Material	ABS + PC
	Color	White