

		<b>Key features</b>	
		<ul style="list-style-type: none"> <li>★ 4K smart dual light bullet network camera</li> <li>★ 4mm@F1.6 lens brings everything back to life</li> <li>★ Efficient H.265+ compression technology</li> <li>★ Motion detection 2.0 with human &amp; Vehicle Detection</li> <li>★ Clear day and night vision with 3D DNR and 120DB WDR</li> <li>★ Built-in microphone for real-time audio security</li> <li>★ Support on-board storage up to 512 GB (SD card slot)</li> <li>★ IP67 Dust and Waterproof Rating</li> <li>★ Support PoE &amp; DC12V</li> </ul>	
<b>Model Number</b>		<b>I91DF</b>	
<b>IP Camera</b>			
Camera	Image Sensor	1/2.4" Progressive Scan CMOS	
	Max resolution	3840*2160(8MP)	
	Main Stream	50 Hz: 12.5fps@3840*2160, 20 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 15fps@3840*2160, 20 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)	
	Substream	50 Hz: 20 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 20 fps (1280 × 720, 640 × 480, 640 × 360)	
	Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG	
	Video Bitrate	32 Kbps - 16 Mbps	
	Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/ AAC-LC	
	Audio Input	Built-in Microphone, record with audio	
	Lens	4 mm	
	Min. Illumination	Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR	
	Angle of View	Horizontal FOV 78°, vertical FOV 38°, diagonal FOV 96°	
	Supplement Light Type	Smart Dual-Light, IR, White Light	
	Supplement Light Range	Up to 30 m	
	Motion detection 2.0	Support, include Human & Vehicle detection	
	Image Enhancement	BLC, HLC, 3D DNR	
	Wide Dynamic Range	120 dB WDR	
	Protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP, UPnP	
	API	Open Network Video Interface Version (Profile S, Profile T, Profile G)	
	Region of Interest (ROI)	1 fixed region for main stream	
	Privacy Mask	4 programmable polygon privacy masks	
General Function	Rotate mode, mirror, password protection, remote access		
Ethernet	1 RJ45 10 M/100 M self-adaptive Ethernet port		
General	Housing	Metal & Plastic	
	Color	White	
	Storage	Built-in microSD/SDHC/SDXC Slot, up to 512 GB	
	Hardware Reset	Yes	
	Operating Power	DC 12 V± 25%, max. 5 W; PoE (802.3af), max. 6.5 W	
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C	
	Indoor/Outdoor Use	Indoor/Outdoor	
	Interface Protection	IP67 & IK08	
	Dimension (L X W X H)	Ø121.4 mm × 97.6 mm (Ø4.78" × 3.84")	
	Weight	1.2 lb./550 g	