

## Key features

2.4GHz Digital Wireless Baby Monitor \*5" TFT LCD monitor,1080P camera. \*Support up to 256GB TF Card, video playback 720P

\*Max upto 1000ft transmission range in open area \*Pan 355° /Tilt 55° roatation controllable, 2X digital zoom \*Ruilt in 4000mAh battery, over 8 hours working time

\*Built in 4000mAh battery, over 8 hours working time
\*Support temperature detection, sound detection (VOX), time alert

\*Support two way audio talking, max 5M IR night vision, play lullaby songs

Model Number		L4154+C127
Camera	Image Sensor	1/4"
	Effective pixel	1920*1080
	Horizontal Viewing Angle	75° (±5°)
	Minimum Illumination	>8 (LED OFF) /<3 (LED ON)
	IR range	5M
	Rotation angel	Pan:355° Tilt:55°
	Interface	Set Button USB Type-C
	Support two-way intercom	Two-way intercom
	Temperature detection range	$32104^{\circ}\text{F}/040^{\circ}\text{C}$ , Temperature accuracy: $\pm 1$
	POWER	5V 1A
	Power consumption	4. 1W (max)
Monitor	Display sieze	5″ TFT LCD
	Screen resolution	1280*720
	Storage Forma	AFS
	Storage Video Resolution	1920*1080
	Support recording mode	Mobile detection side, manual
	Support display mode	Single, Dual, Quad mode
	Support number of camera	Connect Up to 4 Cameras
	Image zoom	×1.5 ×2
	Support two-way intercom	Two-way intercom
	Interface	USB Type-C
	Supports max storage TF car	256GB TF Card
	Battery	4000mAh
	Battery life	Bright screen work: ≤8.0 Screen off work: ≤13.0
	POWER	DC5V 2A
	Power consumption	1.6W-4.2W(Recharge)
RF Characteristics	RF range	2400-2483. 5MHz
	Wireless Transmision	1000ft (max)
General	Operation Temperature	32-104°F/0-40°C
	Storage Emperature	14-140°F/-20-60°C
	Operation Humidity	15%~85%
l .		Packaging Contents
Monitor		1
Camera		1
DC5V 1A Power Adapter (Camera)		1
DC5V 2A Power Adapter (Monitor)		1
Camera bracket		1
Camera bracket screw bag		1
User manual		1
Reset pin		1
· · · · · · · · · · · · · · · · · · ·		