

**Key features**

- Up to 64-ch IP cameras can be connected (up to 12 MP)
- Connectable to the third-party network cameras
- Up to 2-ch@32MP/8-ch@8MP decoding capacity
- H.265+ compression effectively reduces the storage space by up to 75%
- HDMI1/VGA1 and HDMI2/VGA2 outputs provided
- HDMI1 Video output at up to 8K or 4K resolution
- Up to 8 SATA interfaces and 1 eSATA interface for HDD connection, and 14TB capacity for each HDD
- Up to 400 Mbps incoming bandwidth and 400 Mbps outgoing bandwidth
- Supports special cameras, including people counting camera, ANPR (automatic number plate recognition) camera, and fisheye camera
- Advanced streaming technology enables smooth live view in poor network conditions
- 2 self-adaptive 10/100/1000 Mbps Ethernet interfaces
- Supports RAID 0, 1, 5, 6, 10 and N+M hot spare for even more reliable data storage, effectively avoids data loss risks



**Model Number**

**N951BC**

**NVR**

Video & Audio	Decoding Format	H.264+/H.264/H.265/H.265+
	IP Video Input	64-ch
	Video Output	HDMI 1 up to 8K, HDMI 2 up to 4K, VGA 1 & VGA 2 up to 1080p, CVBS
	Audio Input/Output	2/1 RCA
	Incoming & Outgoing Bandwidth	400/400Mbps
	Recording Resolution	32 MP/24 MP/12 MP/8 MP/7 MP/6 MP/5 MP/4 MP/3MP/1080p
	Synchronous Playback	16-CH
	Decoding Capability	2-ch@32 MP (30 fps)/8-ch@8 MP (30 fps)/16-ch@4 MP (30 fps)/32-ch@1080p (30 fps)
	Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2/PCM
	Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Hard Drive	HDD	8 SATA Interface, 1 eSATA interface
	HDD Capacity	Up to 14 TB Capacity for Each HDD
	RAID Type	RAID0, RAID1, RAID5, RAID6, RAID10
External Interface	Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
	Serial Interface	1 RS-485 (full-duplex), 1 RS-232
	Alarm Input/Output	16/9
	Power output	Ctrl 12V 1A& DC 12V 1A
	USB	Front panel: 2 × USB 2.0; Rear panel: 2 × USB 3.0
General	Operating Power	100 to 240 VAC, 50 to 60 Hz
	Max. Power	200 W
	Power Consumption	≤ 50 W (without HDD)
	Chassis	2U chassis
	Working Temperature	14 °F ~ 131 °F/-10 °C ~+55 °C
	Dimensions (W X H X D)	445 × 465 × 93 mm ( 17.5"× 18.3" × 3.7")
	Weight (Without Hard Disk)	≤ 10 kg (22 lb)