



SAFETY DATA SHEET

1. Identification

Product identifier	STEEL-IT 4210B Epoxy Precoat, Part B
Other means of identification	
SDS number	SDS-4210B
Product code	FGPR4210B-P (pint), FGPR4210B-Q (quart), FGPR4210B-G (gallon), FGPR4210B-5G (5-gallon pail)
Recommended use	Paint / Industrial coating (precoat). Category: Pigmented metallic coating.
Recommended restrictions	Uses other than the recommended use.
Manufacturer/Importer/Supplier/Distributor information	
Company name	Stainless Steel Coatings, Inc.
Address	835 Sterling Road Lancaster MA 01523-2915, USA
Telephone	978-365-9828
E-mail	sds@STEEL-IT.com
Emergency telephone	CHEMTREC: 1-800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1A
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, repeated exposure (inhalation)	Category 1 (lungs)
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system, hearing organs, kidneys, liver)
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word

Danger

Hazard statement

Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. Causes damage to organs (lungs) through prolonged or repeated exposure by inhalation. May cause damage to organs (central nervous system, hearing organs, kidneys, liver) through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide to extinguish. Collect spillage.

Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Talc	14807-96-6	30 - 40
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1	20 - 30
2-Butoxyethanol	111-76-2	5 - 15
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	5 - 15
Xylene	1330-20-7	5 - 15
Ethylbenzene	100-41-4	1 - 5
Triethylenetetramine	112-24-3	< 1

Composition comments

The exact percentage (concentration) of composition has been withheld as a trade secret.

All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Jaundice. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed such as: Carbon oxides. Aldehydes. Nitrogen oxides. Fumes of metal oxides. Halogenated compounds.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors/spray. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Retain and dispose of contaminated wash water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors/spray. Do not get in eyes and avoid contact with skin and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Persons susceptible to allergic reactions should not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m ³
		50 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m ³
		100 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m ³
		100 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Talc (CAS 14807-96-6)	TWA	0.1 mg/m ³	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m ³	
		5 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m ³	
		125 ppm	
	TWA	435 mg/m ³	
		100 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable.
Xylene (CAS 1330-20-7)	STEL	655 mg/m ³	
		150 ppm	
	TWA	435 mg/m ³	
		100 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Triethylenetetramine (CAS 112-24-3)	TWA	6 mg/m ³
		1 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2)

Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US WEEL Guides: Skin designation

Triethylenetetramine (CAS 112-24-3)

Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

When working with liquids wear splash-proof chemical goggles and face shield unless full facepiece respiratory protection is worn.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Nitrile or butyl rubber gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Skin protection

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge and full facepiece. Follow OSHA respirator regulations (29CFR 1910.134) and use NIOSH/MSHA approved respirators. Check with respiratory protective equipment suppliers.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing must not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Color

Light tan.

Odor	Characteristic of solvents.
Odor threshold	Not determined.
pH	Not applicable (the material is non-polar/aprotic).
Melting point/freezing point	Property has not been measured.
Initial boiling point and boiling range	280 - 371 °F (137.78 - 188.33 °C)
Flash point	82 °F (27.78 °C)
Evaporation rate	Slower than ether.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1 % v/v
Explosive limit - upper (%)	Property has not been measured.
Vapor pressure	Property has not been measured.
Vapor density	> 1 (Air=1)
Relative density	1.289 (Water=1) (77 °F (25 °C))
Solubility(ies)	
Solubility (water)	2 g/100 g, Moderately soluble in water.
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.
Auto-ignition temperature	Property has not been measured.
Decomposition temperature	Property has not been measured.
Viscosity	Property has not been measured.
Other information	
Density	Property has not been measured.
Explosive properties	Not explosive.
Kinematic viscosity	Property has not been measured.
Oxidizing properties	Not oxidizing.
Particle size	Not applicable, material is a liquid.
VOC	364.5 g/l Test Method: Product Formulation Data

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Protect against direct sunlight. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Strong reducing agents. Halogens.
Hazardous decomposition products	Thermal decomposition of this product can generate carbon monoxide and carbon dioxide. Aldehydes. Nitrogen compounds. Fumes of metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes skin irritation. May cause an allergic skin reaction. May be harmful in contact with skin. May be absorbed through the skin. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Causes serious eye damage.

Ingestion

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Narcosis. Behavioral changes. Decrease in motor functions. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Jaundice. Prolonged exposure may cause chronic effects.

Information on toxicological effects**Acute toxicity**

Harmful if inhaled. May be harmful in contact with skin.

Components**Species****Test Results**

Ethylbenzene (CAS 100-41-4)

Acute**Dermal**

LD50

Rabbit

15400 mg/kg

Inhalation

LC50

Rat

17.4 mg/l, 4 hours

Oral

LD50

Rat

3500 - 4700 mg/kg

Talc (CAS 14807-96-6)

Acute**Oral**

LD50

Rat

> 5000 mg/kg

Triethylenetetramine (CAS 112-24-3)

Acute**Dermal**

LD50

Rabbit

805 mg/kg

Xylene (CAS 1330-20-7)

Acute**Oral**

LD50

Rat

3523 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization**Respiratory sensitization**

Not a respiratory sensitizer.

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2)

3 Not classifiable as to carcinogenicity to humans.

Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)

2B Possibly carcinogenic to humans.

Ethylbenzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity

Not classified. However: Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure	Causes damage to organs (lungs) through prolonged or repeated exposure by inhalation. May cause damage to organs (central nervous system, hearing organs, kidneys, liver) through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.
Further information	Symptoms may be delayed.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
2-Butoxyethanol (CAS 111-76-2)			
Aquatic			
Algae	NOEC	Pseudokirchnerella subcapitata	286 mg/l, 72 hours
Crustacea	EC50	Daphnia magna	835 mg/l, 48 hours
<i>Acute</i>			
Fish	LC50	Oncorhynchus mykiss	1474 mg/l, 96 Hours
Ethylbenzene (CAS 100-41-4)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	1.81 - 2.38 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4.2 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	EC50	Ceriodaphnia dubia	3.6 mg/l, 7 days
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)	
2-Butoxyethanol (CAS 111-76-2)	0.83
Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)	3.6
Ethylbenzene (CAS 100-41-4)	3.15
Xylene (CAS 1330-20-7)	3.12 - 3.2

Mobility in soil The product is partially soluble in water.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential. This product contains one or more substances identified as hazardous air pollutants (HAPs) per the US Federal Clean Air Act (see section 15).

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T2, TP1, TP29
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	Yes
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1263
UN proper shipping name	PAINT
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, <u>S-E</u>
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6) 0.1 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

- Flammable (gases, aerosols, liquids, or solids)
- Acute toxicity (any route of exposure)
- Skin corrosion or irritation
- Serious eye damage or eye irritation
- Respiratory or skin sensitization
- Carcinogenicity
- Specific target organ toxicity (single or repeated exposure)
- Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-Butoxyethanol	111-76-2	5 - 15
Ethylbenzene	100-41-4	1 - 5
Xylene	1330-20-7	5 - 15

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)
Ethylbenzene (CAS 100-41-4)
Talc (CAS 14807-96-6)
Triethylenetetramine (CAS 112-24-3)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)
Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)
Ethylbenzene (CAS 100-41-4)
Talc (CAS 14807-96-6)
Triethylenetetramine (CAS 112-24-3)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)
Ethylbenzene (CAS 100-41-4)
Talc (CAS 14807-96-6)
Triethylenetetramine (CAS 112-24-3)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2)
Ethylbenzene (CAS 100-41-4)
Talc (CAS 14807-96-6)
Xylene (CAS 1330-20-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, 1-chloro-4-(trifluoromethyl)-, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6) Listed: June 28, 2018
Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004
Quartz (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)

Listed: January 1, 1991

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Butoxyethanol (CAS 111-76-2)

Benzene, 1-chloro-4-(trifluoromethyl)- (CAS 98-56-6)

Ethylbenzene (CAS 100-41-4)

Talc (CAS 14807-96-6)

Xylene (CAS 1330-20-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 24-November-2021**Revision date** -**Version #** 01**NFPA ratings****Disclaimer**

Stainless Steel Coatings, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.