

Solar Control & Energy Savings

Spectra Select 20



Performance data	VS 20 SR CDF	
	Single Pane	Dual Pane
Solar Energy Transmission	13%	12%
Solar Energy Reflection-Exterior	49%	47%
Solar Energy Absorption	38%	41%
Visible Light Transmission	21%	20%
Visible Light Reflection-Exterior	47%	48%
Visible Light Reflection-Interior	32%	33%
UV Transmission	<1%	
Shading Coefficient	0.24	0.38
Emissivity	0.52	0.52
U-Value (EN673W/m2K)	4.96	2.52
Glare Reduction	77%	76%
Coefficient of Total Energy Transmission (g-value)	0.21	0.33
Total Solar Energy Rejected	79%	67%
Colour Rendering	93%	93%

10
Year
Limited
Warranty*

Solar Control & Energy Savings

Spectra Select 20



VS 20 SR CDF

Characteristics & benefits

- Good heat control to help give your air conditioner a break
- Rejects up to 79% of solar energy, helping reduce heat build-up and energy costs, while helping to increase occupant comfort
- Durable scratch-resistant coating for easy cleaning
- Shields >99% of UV rays (300-380nm), helping to reduce fading of valuables, fabrics and furnishings
- Eye-comforting glare reduction
- Interior installation

www.llumar.com/emea

EASTMAN

*Certain restrictions apply; see dealer for warranty details.

©2022 Eastman Performance Films, LLC. All rights reserved. No liability is accepted for errors. 12/22