

Solar Control & Energy Savings

Spectra Select 30



| Performance data | VS 30 SR CDF | |
|--|--------------|-----------|
| | Single Pane | Dual Pane |
| Solar Energy Transmission | 16% | 15% |
| Solar Energy Reflection-Exterior | 48% | 46% |
| Solar Energy Absorption | 36% | 39% |
| Visible Light Transmission | 26% | 25% |
| Visible Light Reflection-Exterior | 44% | 45% |
| Visible Light Reflection-Interior | 37% | 37% |
| UV Transmission | <1% | |
| Shading Coefficient | 0.27 | 0.40 |
| Emissivity | 0.53 | 0.53 |
| U-Value (EN673W/m2K) | 4.91 | 2.50 |
| Glare Reduction | 71% | 70% |
| Coefficient of Total Energy Transmission (g-value) | 0.24 | 0.35 |
| Total Solar Energy Rejected | 76% | 65% |
| Colour Rendering | 93% | 92% |

10
Year
Limited
Warranty*

Solar Control & Energy Savings

Spectra Select 30



VS 30 SR CDF

Characteristics & benefits

- Good heat control to help give your air conditioner a break
- Rejects up to 76% of solar energy, helping reduce heat build-up and energy costs, while helping to increase occupant comfort
- Durable scratch-resistant coating for easy cleaning
- Shields >99% of UV rays (300-380nm), helping to reduce fading of valuables, fabrics and furnishings
- Eye-comforting glare reduction
- Interior installation

www.llumar.com/emea

EASTMAN

*Certain restrictions apply; see dealer for warranty details.

©2022 Eastman Performance Films, LLC. All rights reserved. No liability is accepted for errors. 12/22