



SPECIFICATIONS

Application: Heavy Commercial/Healthcare/Marine

Martindale Abrasion: Greater than 100,000 rubs

FR Properties AS1530.3: Smoke Developed Index = 5

Colourfastness to Light (ISO 105-B02): 6 - 7

Composition: 85% PVC 15% Polyester

Pattern Repeat: Plain **Railroaded:** No

Width/Roll Length: 137cm/30m

Care Label: C

Warranty*: 3 Year

*Conditions Apply




Scan the QR Code with your device to view the Pellan Ultimate range and order free sample cuttings.

COLOURWAYS



AVOCADO




AZURE




BALI



BAMBOO



BLACK



BLUE FOG



BOTTLE GREEN



BURGUNDY




CEMENT



COCO



CRETE




DOVE



FALCON



IRIS



JAFFA ORANGE



KOI



MARS RED



MONDO



MUDD



OASIS



PLUM PERFECT




PUTTY



RASPBERRY



SCARLET



STUCCO




TEMPEST



TILANSIA



TRUE BLUE



VIENNA



WHITE CAP



Scan the QR Code with your device
to view the Pellan Ultimate range and
order free sample cuttings.

SPECIFICATIONS

Application	Heavy Commercial, Healthcare, Hospitality & Marine Upholstery
Abrasion Resistance	Test method AS 2001.2.25 (12kPa) Martindale Method No significant wear after 100,000 + Rubs
Anti Microbial & Anti Bacterial	Sanitised to inhibit growth of Mould and Bacteria
Composition	85% PVC 15% Polyester Gauge: 1.0mm Roll Length: 30m Roll Width 137cm
Colour Fastness to Light	UV Stabilised and suitable for indoor/outdoor use. Light Fastness rating 6-7 ISO 105-B02-1994 (Grey Scale 1-5)
Colour Fastness to Bleach	Tested to Australian Standards (AS2001.4) No change of colour rating 4-5
Meets FR Standards for use in Commercial Areas:	FR Properties: Tested to Australian Standards(AS1530.3) Spread of Flame: 0 Smoke Developed: 5, IMO Standards A. 652(16) AS/NZS 3837
Reach Certification	Compliant with the EU Reach regulation (EC) No 1907/2006 The Reach Certification restricts the use of harmful chemicals that potentially have an impact on both human health & the environment. Pellan Ultimate is Phthalate Free. No Formaldehyde, Lead, Mercury or Chromium used in the manufacturing process.
Protech	A protective top surface allowing easy removal of stains and dirt
Care & Cleaning	Most stains can be cleaned using warm soapy water, followed by clean water rinsing. Moderate scrubbing with a medium bristle brush will help loosen soiling from the embossed surface. Failure to follow cleaning instructions may permanently stain and reduce the life of the vinyl.