TESSUTO classic

Commercial Upholstery Fabric

TESSUTO classic captures the look and feel of woven fabric whilst providing the durability and care of a vinyl.

The outstanding performance of TESSUTO classic makes it a good choice for use in high traffic areas, especially in hotels, restaurants, hospitals and educational facilities.

TESSUTO classic is U.V. resistant which enables the vinyl to withstand extreme outdoor conditions. The vinyl fabric is also treated with Protech coating, a formulation which helps guard against stains and inhibits the growth of bacteria in healthcare environments.





TESSUTO classic

Commercial Upholstery Fabric







TESSUTO classic

Commercial Upholstery Fabric

SPECIFICATIONS

85% PVC 15% Polyester Gauge: 1.0mm Roll length: 30m Roll width: 137cm. Composition

Abrasion resistance Test method AS 2001.2.25 (12kPa) Martindale method. No significant wear after 50,000+ rubs.

Meets F.R. standards for F.R. properties: Tested to Australian Standards (AS 1530.3)

Spread of flame: 0 Smoke developed: 5 use in commercial areas

I.M.O. Standards A. 652 (16) AS/NZS 3837

Fire test certificates available upon request.

Sanitised to inhibit growth of bacteria, mould & mildew.

& anti-bacterial

Colour fastness to light Tessuto classic is UV stabilized and suitable for indoor and outdoor use. Light fastness rating 6-7

ISO 105-B02-1994 (Grey scale 1-5).

Colour fastness to bleach Tested to Australian Standards (AS 2001.4.11)

No change of colour rating 4-5.

REACH certification Tessuto classic is compliant with the EU REACH regulation (EC)

> No 1907/2006 – The REACH certification restricts the use of harmful chemicals that potentially have an impact on both human health and the environment. TESSUTO is Phthalate free.

No formaldehyde, lead, mercury & chromium is used in the

manufacturing process.

Protech A protective top surface allowing easy removal of difficult

stains and dirt.

Suitable for heavy commercial, healthcare and Usage

marine upholstery.

CARE & CLEANING

Most stains can be cleaned using warm soapy water, followed by clean water rinsing. Moderate scrubbing with a medium bristle brush will help loosen soiling from the embossed surface. Failure to follow cleaning instructions may permanently stain and reduce the life of the vinyl. For further cleaning information, please contact Austex Fabrics for a product



All Austex products are designed and manufactured in accordance with the quality assurance system ISO 9001.











UV STABILISED







ENVIRONMENTALLY FRIENDLY





EXCLUSIVELY DISTRIBUTED BY:





