



A patented performance fabric, Crypton Super Fabric is perfect for demanding environments. Providing heavy-duty durability, unparalleled liquid, stain and odor resistance, plus an impenetrable moisture barrier, Crypton allows products to stay beautiful and last longer.

All Crypton Super Fabrics endure rigorous performance testing and must meet or exceed the minimum standards listed below.

PERFORMANCE FEATURES AND SPECIFICATIONS



| Fiber Content: | 100% Polyester | | |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Width: | 54" (1370mm) | | |
| Pattern Repeat: | H: 4.5cm V:3.5cm | | |
| Weight: | Approx 455g/m2 | | |
| Warranty | 3 Year | | |
| Repellency: | Spray Rating Aqueous Liquid Repellency: Water/Alcohol Solution Resistance Oil Repellency: Hydrocarbon Resistance | AATCC 22 AATCC 193 AATCC 118 | 80-100 of 100 max 6 ± 1 6 ± 1 |
| Cleanibility: | Spot-Cleaning/Stain Resistance: With Water and Mild Detergent (1% Dishwashing Liquid or Laundry Deterge Durable to a Variety of pH-Neutral Cleaners and Disinfectants Do Not Use Solvent Cleaners | nt) | 4-5 of 5 max 4-5 of 5 max |
| Moisture Barrier: | Hydrostatic Resistance | AATCC 127 | ≥100 cm |
| Odor-Resistant Silver Ion Technology: | Fabric is Protected from Odors and Microbial Damage Bacteria Resistance Fungal Growth Resistance | ISO 20743 AATCC30 | 95% ± 5% 95% ± 5% |
| Abrasion & Pilling Resistance: | Oscillatory Cylinder Method Martindale Abrasion Martindale Pilling | ASTM D 4157 (cotton duck) ASTM D 4966/ISO 12947-2 ASTM D4970 ISO 12945-2 (415g) | ≥ 50k Double Rubs ≥ 40k Cycles ≥ Class 3 ≥ Class 3 |
| Colorfastness to Light: | Xenon Arc Lamp Method | AATCC 16 Option 1 or 3 ISO 105-B02 | ≥ Class 4 at 40 hrs ≥ Class 4 at 40 hrs |
| Flammability: | Methods for Fire Tests on Building Materials Component and Structure: Part 3: Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release | AS/NZS 1530.3-1999 | Ignitability Index 12 Spread of Flame Index 0 Heat Evolved Index 3 Smoke Developed Index 5 |

Environmental: Third-Party Tested for VOCs - Compliant to California Section 01350

GREENGUARD Gold Certified

 $\label{thm:problem} \textit{Free of Potentially Harmful Levels of PFOS}, \textit{PFOA}, \textit{Formaldehyde}, \textit{Heavy Metals}, \\$

Phenols, Phthalates, Odor and Skin Sensitizers - No Additional FRs

(International FR requirments can be met upon request)

Can Be Recycled CA Prop 65-Compliant

Crypton Inc.'s Manufacturing and Raw Materials are SCS Validated to NSF 336

Exclusively Distributed by



Wortley Group 25 Geddes St, Mulgrave VIC 3170 Created on: 27/2/20 Website: www.wortleygroup.com,au Email: sales@wortleygroup.com.au

Phone: 1300 36 18 36



COLOURWAYS - CRUISE

Complimentary cuttings available via www.wortleygroup.com.au

Please Note: Images are a guide only - refer to actual sample for true colour Pattern is not shown to scale



Website: www.wortleygroup.com,au Email: sales@wortleygroup.com.au Phone: 1300 36 18 36

f o y @wortleygroup