



SPECIFICATIONS

Composition: 100% Polyester

Usage: Heavy Commercial - Health/Hospitality

HR: 0cm VR: 0cm

Care Label: E

AS1530.3 Flammability: Yes - Smoke Developed Index: 5

Available Colours: 16

	CLUB APPLE				SAFER
COLOURWA	YS		indicati carenteriaria 1. compati 1. compati	NORMO DA RECEITIVE, GROOM	Mener U.S. (PA Salar Product Salariti
ALUMINUM	APPLE	AVOCADO	BONE	CARIBBEAN	MINK
MUSHROOM	NAVY	PERSIMMON	PORT	PRUSSIAN	SAFFRON
SAND	SILVER FOX	STONE	STORM	WO	RTLEY Furnishing in Style
				Scan the OR Cod	e with your device

Scan the QR Code with your device to view the Club Collection and order free sample cuttings.

Website: www.wortleygroup.com.au Email: sales@wortleygroup.com.au Phone: 1300 36 18 36





SPECIFICATIONS

A patented performance fabric, Crypton Fabric is perfect for demanding environments. Providing heavy-duty unparalleled liquid, stain and odour resistancem plus an imprenetrable barrier, Crypton allows products to stay beautiful and last longer.

All Crypton fabrics endure rigorous performance testing and must meet or exceed the minimum standards list below.

PERFORMANCE FEATURES AND SPECIFICATIONS

Fiber Content:	100% Polyester		
Width:	54" (1370mm)		
Warranty:	3 Year		
Repellency:	Spray Rating Aqueous Liquid Repellency: Water/Alcohol Solution Resistance Oil Repellency: Hydrocarbon Resistance	AATCC 22 AATCC 193 AATCC118	A80-100 of 100 max 6 ± 1 6 ± 1
Cleanibility:	Spot-Cleaning/Stain Resistance: With Water and Mild Detergent (1% Dishwashing liquid or Laundry Detergent) Durable to a variety of pH-Neutral Cleaners and Disinfectants Do not use Solvent Cleaners		4 - 5 of 5 Max 4 - 5 of 5 Max
Moisture Barrier:	Hydrostatic Resistance	AATCC127	≥100 cm
Odor-Resistant Silver Ion Technology:	Fabric is Protected from Odors and Microbial Damage Bacteria Resistance Fungal Growth Resistance	ISO 20743 AATCC30	95% ± 5% 95% ± 5%
Abrasion & Pilling Resistance:	Oscillatory Cylinder Method Martindale Abrasion Martindale Pilling	ASTM D 4157 (cotton duck) ASTM D 4966/ISO 12947-2 ASTM D4970 ISO 12945-2 (415g)	≥ 50k Double Rubs ≥ 40k Cycles ≥ Class 3 ≥ Class 3
Colorfastness to Light:	Xenon Arc Lamp Method	AATCC 16 Option 1 or 3 ISO 105-B02	≥ Class 4 at 40 hrs ≥ Class 4 at 40 hrs
Flammability:	Methods for Fire Tests on Building Materials Component and Structure: Part 3: Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release	AS/NZS 1530.3-1999	Smoke Developed Index: 5
Environmental:	Third-Party Tested for VOCs - Compliant to California Section GREENGUARD Gold Certified Free of Potentially Harmful Levels of PFOS, PFOA, Formaldel Phenols, Phthalates, Odor and Skin Sensitizers - No Addi (International FR requirements can be met upon reques Can Be Recycled CA Prop 65-Compliant Crypton Inc.'s Manufacturing and Raw Materials are SCS Value	Exclusively Distributed by	

