

WALES



WALES LAPIS

SPECIFICATIONS

Composition: 100% Polyester

Usage: Heavy Commercial - Health/Hospitality

HR: 0cm VR: 0cm

Width: 137cm

Care Label: E

AS1530.3 Flammability: Yes - Smoke Developed Index: 5

Available Colours: 12









COLOURWAYS



BAZAAR



DIJON



FIESTA



JEWEL



JUNGLE



LAPIS



MIDNIGHT



MINERAL



OPAL



RUSTIC



SEAGLASS



SEPIA





Scan the QR Code with your device to view the Wales Collection and order free sample cuttings.



SPECIFICATIONS

A patented performance fabric, Crypton Fabric is perfect for demanding environments. Providing heavy-duty unparalleled liquid, stain and odour resistancem plus an imprenetrable barrier, Crypton allows products to stay beautiful and last longer.

All Crypton fabrics endure rigorous performance testing and must meet or exceed the minimum standards list below.

PERFORMANCE FEATURES AND SPECIFICATIONS

| Fiber Content: | 100% Polyester | | |
|---|--|--|---|
| Width: | 54" (1370mm) | | |
| Warranty: | 3 Year | | |
| Repellency: | Spray Rating Aqueous Liquid Repellency: Water/Alcohol Solution Resistance Oil Repellency: Hydrocarbon Resistance | AATCC 22 AATCC 193 AATCC118 | A80-100 of 100 max 6 ± 1 6 ± 1 |
| Cleanibility: | Spot-Cleaning/Stain Resistance: With Water and Mild Detergent (1% Dishwashing liquid or Laundry Detergent) Durable to a variety of pH-Neutral Cleaners and Disinfectants Do not use Solvent Cleaners | | 4 - 5 of 5 Max 4 - 5 of 5 Max |
| Moisture Barrier: | Hydrostatic Resistance | AATCC127 | ≥100 cm |
| Odor-Resistant Silver Ion Technology: | Fabric is Protected from Odors and Microbial Damage Bacteria Resistance Fungal Growth Resistance | ISO 20743 AATCC30 | 95% ± 5% 95% ± 5% |
| Abrasion & Pilling Resistance: | Oscillatory Cylinder Method Martindale Abrasion Martindale Pilling | ASTM D 4157 (cotton duck) ASTM D 4966/ISO 12947-2 ASTM D4970 ISO 12945-2 (415g) | ≥ 50k Double Rubs ≥ 40k Cycles ≥ Class 3 ≥ Class 3 |
| Colorfastness to Light: | Xenon Arc Lamp Method | AATCC 16 Option 1 or 3 ISO 105-B02 | ≥ Class 4 at 40 hrs ≥ Class 4 at 40 hrs |
| Flammability: | Methods for Fire Tests on Building Materials Component and Structure: Part 3: Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release | AS/NZS 1530.3-1999 | Smoke Developed Index: 5 |
| Environmental: | Third-Party Tested for VOCs - Compliant to California Section GREENGUARD Gold Certified | า 01350 | |

Exclusively Distributed by



Can Be Recycled CA Prop 65-Compliant

Crypton Inc.'s Manufacturing and Raw Materials are SCS Validated to NSF 336

Free of Potentially Harmful Levels of PFOS, PFOA, Formaldehyde, Heavy Metals,

Phenols, Phthalates, Odor and Skin Sensitizers - No Additional FRs (International FR requirements can be met upon request)