



## ONE COAT ONLY HS<sup>PLUS</sup>

Twice as much coverage through high oil content - saves time and money!



9211 White Spruce    9212 Silver Poplar    9221 Pine    9232 Mahogany    9234 Scand. Red



9235 Red Cedar    9236 Larch    9241 Oak    9242 Fir Green    9261 Walnut



9262 Teak    9264 Rosewood    9271 Ebony



### PRODUCT DESCRIPTION

Decorative, satin protective wood finish based on natural oils for exterior wood. Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent, extremely weather-resistant and UV-stable. Does not crack, peel, flake or blister. No sanding necessary, just simply recoat. Easy and seamless application. Finish stays workable while coating. Osmo One Coat Only HS<sup>Plus</sup> has a low content of solvents, works without any biocides or preservatives, has a high content of solids and thus offers high product coverage. With only a very thin coat, an optimal surface protection is achieved. When dry, finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and is resistant to saliva and perspiration according to DIN 53160 (German industrial norm).

### RECOMMENDED USE

Osmo One Coat Only HS<sup>Plus</sup> is ideal for the protection of all wood in outdoor areas: carports, timber cladding, balconies, fences, pergolas, garden furniture and summer houses. Well suited to renewing old microporous stains.

### CONTAINS

Based on natural plant oil (sunflower oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and additives. Dearomatized white spirit (benzene-free). Complies with Environment Canada VOC regulations (SOR/2009-264). Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.95-1.2 g/cm<sup>3</sup>  
 Viscosity: 18-26s DIN EN ISO 2431/4 mm, viscid  
 Odour: faint/mild, after drying odourless  
 Flash point: >61°C acc. DIN EN ISO 2719

### STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20%).  
 Osmo One Coat Only HS<sup>Plus</sup> is ready to use, please do not thin. Stir well before use.  
 Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works.



The finished surface is influenced by several factors, including the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces.

If additional protection against blue stain, rot and insects is desired, pre-treat the wood if possible on all sides with Osmo WR Base Coat.

## DIRECTIONS FOR USE

With Osmo Flat Brush or Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and spread well.

Allow to dry for approx. 12 hours under good ventilation.

## CLEANING OF TOOLS

With Osmo Brush Cleaner and Thinner (free of aromatic compounds).

## DRYING TIME

Approx. 12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

## COVERAGE

1 litre covers approx. 280 ft<sup>2</sup> (26 m<sup>2</sup>) with one coat. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

## NOTE

The transparent colour tone is influenced by the natural tone of the wood and may deviate from the colour chart. When applied too generously, glossy spots may appear. With time, these glossy spots will weather automatically into an even satin look.

Light-coloured transparent finishes offer only limited UV protection (greying and bleaching out through sunrays) and are therefore not recommended for surfaces exposed to strong sunlight.

If exterior surfaces (e.g. windows, doors) should have extra protection, apply 1 final top coat of Osmo UV-Protection-Oil Extra Clear (410 without film protection or 420 with film protection) after thoroughly drying. This protects against dirt and stains and extends the life of the coating.

For One Coat Only HSPlus Spruce White 9211, please use Natural Oil Woodstain White 900.

Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

## HAZARD STATEMENTS



### CAUTION

READ INSTRUCTIONS BEFORE USING

### DANGER OF COMBUSTION

Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Use only in a well-ventilated area. Keep away from flames or sparks. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard. **FIRST AID TREATMENT.** Contains aliphatic hydrocarbons. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

### DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

### COLOUR TONES

- 9211 White Spruce
- 9212 Silver Poplar
- 9221 Pine
- 9232 Mahogany
- 9234 Scandinavian Red
- 9235 Red Cedar
- 9236 Larch
- 9241 Oak
- 9242 Fir Green
- 9261 Walnut
- 9262 Teak
- 9264 Rosewood
- 9271 Ebony

### CAN SIZES

750mL; 2.50 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 10/17