



WOOD REVIVER POWER-GEL

Cleans and refreshes grayed wood effectively!



6609
Clear

PRODUCT DESCRIPTION

Gelatinous cleaner for refreshing and cleaning grayed exterior wood. Wood Reviver Power-Gel is a non-drip product, which makes it easy to apply – especially on vertical surfaces. The gel penetrates the wood deeply and removes the gray patina. By re-oiling afterward, the fresh warm wood color is restored.

RECOMMENDED USE

Osmo Wood Reviver Power-Gel is highly recommended for wood decks, siding, garden furniture and other exterior wood surfaces.

CONTAINS

Osmo Wood Reviver Power-Gel contains biodegradable oxalic acid (< 5 %). This product is free of solvents, formaldehyde, chlorine compounds and amines. Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.99-1.05 g/cm³
 Viscosity: > 70s DIN EN ISO 2431/3 mm, thixotropic
 Odour: faint/mild, after drying odourless
 Flash point: not applicable

STORAGE

Up to 2 years and longer if container is kept dry, closed tightly and stored at temperatures between 41 and 95 °F. Do not expose to frost during transport!

PREPARATION

Before the application, remove debris from grayed wood and dampen surface with water. A trial application is recommended before treating wood with Wood Reviver Power-Gel.



DIRECTIONS FOR USE

Wood Reviver Power-Gel is ready to use. Do not thin. Apply gel generously along the wood grain. After approx. 20 minutes' reaction time, clean surface with Osmo Decking Cleaning Brush and rinse with generous amount of water. After drying for approx. 48 hours, protect the newly refreshed wood surface with a wood finish, such as Osmo Natural Oil Woodstain, Decking-Oils, Country Colour.

For machine applications on decking, we recommend Osmo Decking and Flooring Cleaner.

CLEANING OF TOOLS

Clean working tools with soap and water directly after use.

DRYING TIME

Approx. 24-48 hours (normal climatic conditions, 73 °F/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

COVERAGE

1 Liter covers approx. 107-215 sq. ft. with one application. Coverage will vary depending on the type, age and texture of the wood.

NOTE

Avoid direct contact to metal and plants. Cover plants and hinges with tarpaulins.



CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines. Only completely emptied cans can be recycled.

COLOR TONES

6609 Clear

CAN SIZES

0.5 L; 2.50 L; 5.00 L; 10.00 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 06/18