





SPEC	N4
• Model	RH/LH
• Gear Ratio	4.4:1
• Bearings	4
• Weight	810g (29oz)
• Max Drag	10kg (22 <i>lb</i>)
• Line Retrieve	100cm (39in)
Braid Capacity	#1.5: 1600m (16lb: 1750yd) #2.0: 1200m (18lb: 1300yd) #2.5: 1000m (20lb: 1100yd) #3.0: 800m (30lb: 850yd) #4.0: 600m (40lb: 650yd)

SPEC	S 5
• Model	RH/LH
• Gear Ratio	4.4:1
• Bearings	4
• Weight	845g (30oz)
• Max Drag	10kg (22 <i>lb</i>)
• Line Retrieve	100cm (39in)
Braid Capacity	#1.5: 2000m (16lb: 2200yd) #2.0: 1500m (18lb: 1650yd) #2.5: 1200m (20lb: 1300yd) #3.0: 1000m (30lb: 1100yd) #4.0: 750m (40lb: 800yd) #5.0: 600m (50lb: 650yd)

SPEC	W6
• Model	RH/LH
• Gear Ratio	4.4:1
• Bearings	4
• Weight	865g (31 <i>oz</i>)
• Max Drag	10kg <i>(22lb)</i>
• Line Retrieve	100cm (39in)
Braid Capacity	#2.0: 1800m (18lb: 2000yd) #2.5: 1500m (20lb: 1650yd) #3.0: 1200m (30lb: 1300yd) #4.0: 900m (40lb: 1000yd) #5.0: 700m (50lb: 750yd) #6.0: 600m (60lb: 650vd)

Marfix

Product of Japan Distributed by SPRO USA





Marfix

WHAT IS Marfix?

• Model RH/LH

• Gear Ratio 4.8:1

• Bearings 7+1

• Weight 660g (23oz)

• **Max Drag** 8kg (18lb)

• **Line Retrieve** 100cm (39in)

• Braid Capacity #1.5: 1200m (16lb: 1300yd)

#2.0: 900m (18lb: 1000yd) #2.5: 700m (20lb: 750yd)

#3.0: 600m (30lb: 650yd)

Precision Manufacturing

Marfix is renowned worldwide for its durability. All Marfix models use a one-piece aluminum body with as few seams as possible. The high-strength stainless steel gear reduces strain on anglers while jigging and while fighting big fish. All of this explains why so many Marfix reels from years past are still in use in the field today.

Smooth Lever Drag

Marfix reels are equipped with a largediameter drag washer that remains smooth even when generating heavy drag force.

Consistent Winding

Marfix sets the maximum line retrieve per crank for all of their reels to 100cm (~39in), providing a consistent standard that enhances fishing outcomes.

Marfix

Product of Japan Distributed by SPRO USA

