



LMR BATTERY SPECIFICATIONS	PART NUMBER
	WV- LEKNBL2LIIS

COMPATIBLE RADIOS	Kenwood NX5200, NX5300, NX5400, TK5230, TK5330, TK5430, VP5230, VP5330, VP5430, VP6230, VP6330, VP6430
REPLACES OEM BATTERY	KNB-LS5 (2000 mAh)
CERTIFICATION	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5th Edition standard for intrinsically safe use (Class I, II, III / Division 1 / Groups A-G / -20° C to 60° C, T3B) and non-incendive use (Class I, II, III / Division 2 / Groups A-G / -20° C to 60° C, T3B)
COMPATIBLE CHARGERS	Endura EC1-KW4A, EC1M-KW4A, EC6M-KW4A, EC2M-KW4A-D, EC12M-KW4A-D / Logic LEVCA-KW4 / Kenwood KSC-32
VOLTAGE / CAPACITY	7.4V / 3400 mAh
CHEMISTRY / CELL TYPE	Li-Ion / Panasonic UF553450Z
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +45° C (charge)
CHARGE CYCLES	>450
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (conditioning not required for cycle life or battery run time)
PROTECTION TYPES	Over-charge / over-discharge / over-temperature
HOUSING MATERIAL / SEAL	AE8000 ABS (UL 94) / ultrasonic weld
INGRESS PROTECTION	IP67 rated
METAL WELDING	Pure nickel tabs w/ spot welder
DIMENSIONS / WIEGHT	4.59" x 2.28" x 1.11" (116.5 x 57.9 x 28.2 mm) / 0.42 lbs. (190.5 g)
WARRANTY	12 months (capacity 80%) 12 months (materials and workmanship)
PRODUCT PHOTO	