


LMR BATTERY SPECIFICATIONS	PART NUMBER
	WVX-4069IS

COMPATIBLE RADIOS	Motorola XPR6100, XPR6300, XPR6350, XPR6380, XPR6500, XPR6550, XPR6580, Vertex Standard VXD720
REPLACES OEM BATTERY	PMNN4069A
HAZ LOC RATINGS	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5th Edition standard for intrinsically safe use (Class I, II, III / Division 1 / Groups C-G / -20° C to 40° C, T3C) and non-incendive use (Class I, II, III / Division 2 / Groups A-G / -20° C to 40° C, T3C)
INGRESS PROTECTION	IP64 rated
COMPATIBLE CHARGERS	Endura EC1-MT16, EC1M-MT16, EC2M-MT16-D, EC6M-MT16, EC12M-MT16-D / Logic LEVCA-MT16
CONDITIONER COMPATIBLE	N/A
VOLTAGE / CAPACITY	7.4V / 2200 mAh
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic UR18650ZY (Japanese)
OPERATING TEMPERATURE	-20° C to +40° C (discharge, T3C) / 10° C to +45° C (charge)
CHARGE CYCLES	>500
CHARGE TYPE	Rapid
PROTECTION TYPES	Over charge / over discharge / over temperature
HOUSING MATERIAL	ABS
HOUSING SEAL / SEAL	ABS / ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included
WARRANTY	12 months
PRODUCT PHOTO (Brand: Logic Energy)	 <div style="border: 1px dashed black; padding: 5px; margin-left: 200px;"> <p>Dimensions (H x W x D): 5.07" x 2.13" x 0.89" 128.8 mm x 54.0 mm x 22.6 mm</p> </div>