

Waveband Communications

LMR BATTERY SPECIFICATIONS	PART NUMBER
	WV- M9857XTIS

COMPATIBLE RADIOS	Motorola XTS1500, XTS2500, MT1500, PR1500
REPLACES OEM BATTERY	NTN9857C
CERTIFICATIONS & RATINGS	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5 th Edition standard for intrinsically safe use (Class I, II, III, Division 1, Groups C, D, E, F, G, T3C) and non-incendive use (Class I, Division 2, Groups A, B, C, D, T3C). IP64 rated.
COMPATIBLE CHARGERS	Endura IWC1-MT13B, IW C1M-MT13B, IW C2M-MT13-D, IW C6M-MT13B, IWC12M-MT13-D
VOLTAGE/ CAPACITY	7.5V / 2500 mAh
CHEMISTRY	NiMH
CELL TYPE	FOK HR-AU (Japanese)
OPERATING TEMPERATURE	0° C to +50° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid or trickle
CONDITIONER COMPATIBLE	Yes
THERMAL PROTECTION	Yes
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included
WARRANTY	12 months
PRODUCT PHOTO (Brand: Logic Energy)	 