

1 Identification

· **Product identifier**

· **Trade name:** 39023 - 39583 TPO-Direct Bumper Coaters

· **Article number:**

39153, 39253, 39263, 39273, 39163, 39173, 39183, 39193, 39283, 39293, 39413, 39423, 39443, 39583, 39023, 39073, 39083, 39103

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· **Information department:**

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*toluene
cyclohexane
Stoddard solvent
Solvent naphtha (petroleum), light arom.*

· **Hazard statements**

*H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P302+P352 If on skin: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a poison center/doctor if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



(Contd. on page 3)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· Dangerous components:		
115-10-6	dimethyl ether	40-60%
108-88-3	toluene	13-30%
110-19-0	isobutyl acetate	13-30%
110-82-7	cyclohexane	1.5-5%
108-83-8	2,6-dimethylheptan-4-one	1-1.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

USA

(Contd. on page 4)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

115-10-6	dimethyl ether	3,000 ppm
108-88-3	toluene	67 ppm
110-19-0	isobutyl acetate	450 ppm
110-82-7	cyclohexane	300 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
1333-86-4	Carbon black	9 mg/m ³
13463-67-7	titanium dioxide	30 mg/m ³
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m ³
1330-20-7	xylene	130 ppm
78-93-3	butanone	200 ppm
67-63-0	propan-2-ol	400 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
2807-30-9	2-(propyloxy)ethanol	2.2 ppm
100-41-4	ethylbenzene	33 ppm
25068-38-6	bisphenolA(chloro)oxirane polymer	90 mg/m ³
67-56-1	methanol	530 ppm
78-83-1	butanol	150 ppm
57-55-6	Methyl glycol	30 mg/m ³

· **PAC-2:**

115-10-6	dimethyl ether	3800* ppm
108-88-3	toluene	560 ppm
110-19-0	isobutyl acetate	1300* ppm
110-82-7	cyclohexane	1700* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
1333-86-4	Carbon black	99 mg/m ³
13463-67-7	titanium dioxide	330 mg/m ³
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m ³
1330-20-7	xylene	920* ppm
78-93-3	butanone	2700* ppm
67-63-0	propan-2-ol	2000* ppm

(Contd. on page 5)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 4)

108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
2807-30-9	2-(propyloxy)ethanol	24 ppm
100-41-4	ethylbenzene	1100* ppm
25068-38-6	bisphenolA(chloro)oxirane polymer	990 mg/m ³
67-56-1	methanol	2,100 ppm
78-83-1	butanol	1,300 ppm
57-55-6	Methyl glycol	1,300 mg/m ³

· **PAC-3:**

115-10-6	dimethyl ether	7200* ppm
108-88-3	toluene	3700* ppm
110-19-0	isobutyl acetate	7500** ppm
110-82-7	cyclohexane	10000** ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
1333-86-4	Carbon black	590 mg/m ³
13463-67-7	titanium dioxide	2,000 mg/m ³
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m ³
1330-20-7	xylene	2500* ppm
78-93-3	butanone	4000* ppm
67-63-0	propan-2-ol	12000** ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
2807-30-9	2-(propyloxy)ethanol	140 ppm
100-41-4	ethylbenzene	1800* ppm
25068-38-6	bisphenolA(chloro)oxirane polymer	5,900 mg/m ³
67-56-1	methanol	7200* ppm
78-83-1	butanol	8000* ppm
57-55-6	Methyl glycol	7,900 mg/m ³

7 Handling and storage

· **Handling:**

· **Precautions for safe handling** No special measures required.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 6)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 5)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEEL Long-term value: 1000 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm
BEI

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m³, 150 ppm

REL Long-term value: 700 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

110-82-7 cyclohexane

PEL Long-term value: 1050 mg/m³, 300 ppm

REL Long-term value: 1050 mg/m³, 300 ppm

TLV Long-term value: 344 mg/m³, 100 ppm

108-83-8 2,6-dimethylheptan-4-one

PEL Long-term value: 290 mg/m³, 50 ppm

REL Long-term value: 150 mg/m³, 25 ppm

TLV Long-term value: 145 mg/m³, 25 ppm

· **Ingredients with biological limit values:**

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 7)

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 6)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -24 °C

· **Flash point:** -42 °C

(Contd. on page 8)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 7)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	235 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	18.6 Vol %
· Vapor pressure at 20 °C:	5,200 hPa
· Density at 20 °C:	0.78383 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	89.8 %
Water:	0.0 %
VOC content:	89.83 %
	704.1 g/l / 5.88 lb/gl
Solids content:	8.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 9)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 8)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

110-82-7 cyclohexane

Oral	LD50	12,705 mg/kg (rat)
------	------	--------------------

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1333-86-4	Carbon black	2B
13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
67-63-0	propan-2-ol	3
100-41-4	ethylbenzene	2B
14807-96-6	Talc	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5	montmorilontie clay complex
------------	-----------------------------

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 10)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 9)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**

· **DOT**



- **Class** 2.1
- **Label** 2.1

· **ADR**



- **Class** 2 5F Gases
- **Label** 2.1

· **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

(Contd. on page 11)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 10)

· Packing group · DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user · EMS Number: · Stowage Code	Warning: Gases F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· ADR · Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· Section 355 (extremely hazardous substances):	None of the ingredient is listed.
· Section 313 (Specific toxic chemical listings):	
108-88-3	toluene
110-82-7	cyclohexane
7429-90-5	aluminium
	Acrylic Resin
1330-20-7	xylene

(Contd. on page 12)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 11)

78-93-3	butanone
67-63-0	propan-2-ol
100-41-4	ethylbenzene
67-56-1	methanol
14807-96-6	Talc

· **TSCA (Toxic Substances Control Act):**

115-10-6	dimethyl ether
108-88-3	toluene
110-19-0	isobutyl acetate
110-82-7	cyclohexane
108-83-8	2,6-dimethylheptan-4-one
1333-86-4	Carbon black
7429-90-5	aluminium
19549-80-5	4,6-dimethylheptan-2-one
13463-67-7	titanium dioxide
51274-00-1	YELLOW IRON OXIDE
1330-20-7	xylene
78-93-3	butanone
67-63-0	propan-2-ol
1332-37-2	Iron oxide
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
100-41-4	ethylbenzene
25068-38-6	bisphenolA(chloro)oxirane polymer
67-56-1	methanol
68911-87-5	montmorilontie clay complex
61791-55-7	Amines, N-tallow alkyltrimethylenedi-
14807-96-6	Talc
78-83-1	butanol
57-55-6	Methyl glycol
7732-18-5	water

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4	Carbon black
13463-67-7	titanium dioxide
1330-20-7	xylene
100-41-4	ethylbenzene
25068-38-6	bisphenolA(chloro)oxirane polymer

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 13)

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 12)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

67-56-1 methanol

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

108-88-3 toluene

II

110-82-7 cyclohexane

I

1330-20-7 xylene

I

78-93-3 butanone

I

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3 toluene

A4

1333-86-4 Carbon black

A4

7429-90-5 aluminium

A4

13463-67-7 titanium dioxide

A4

1330-20-7 xylene

A4

67-63-0 propan-2-ol

A4

100-41-4 ethylbenzene

A3

14807-96-6 Talc

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4 Carbon black

13463-67-7 titanium dioxide

67-56-1 methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS04

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene

cyclohexane

Stoddard solvent

Solvent naphtha (petroleum), light arom.

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

(Contd. on page 14)



Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 13)

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

• **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Environment protection department.

• **Contact:** Rita Joiner (rjoiner@semproducts.com)

• **Date of preparation / last revision** 03/14/2018 / 4

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 15)



Printing date 03/14/2018

Reviewed on 06/21/2017

Trade name: 39023 - 39583 TPO-Direct Bumper Coaters

(Contd. of page 14)

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
Press. Gas: Gases under pressure – Compressed gas
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

USA