



SABA Primer Marine

primer for (teak) wood

Description

SABA Primer Marine is a 1-component primer for pre-treating wooden (teak) deck sections.

Field of application

The marine sector. SABA Primer Marine is very suitable for pre-treating wooden (teak) deck sections before they are sealed off and the for pre-treating synthetic material deck parts before they are bonded.

Advantages

- resistance against water
- applied primer is visible because of the colour
- short drying time
- long open time

Method of use

For instructions for use, see the relevant info sheets on www.saba.nl

When working with a type of wood which is not specified, please contact your supplier.

Seal the container as soon as possible after use; this has a positive effect on the processing properties and the shelf life of the product.

Technical data

Basis	polyacrylat with silane
Viscosity at 23 °C (EN 12092)	approx. 15 mPa.s
Density (EN ISO 2811-2)	approx. 1010 kg/m ³
Solids content	approx. 31 %
Flashpoint	approx. + 40 °C
Solvents	mixture of alcohol and aromas
Open time	30 minutes to 20 hours
Coverage	approx. 100 g/m ²
Working temperature	min. + 5 °C to max. + 35 °C
Storage temperature	min. + 5 °C to max. + 25 °C
Temperature resistance	min. - 30 °C to max. + 70 °C

Order information

Packaging	can with resealable lid
Contents	500 ml (contains 12 items)
Colour	black
Article no.	100672 AAT
Shelf life	18 months (in unopened packaging)

Other packaging on request. The shelf life may vary for large packaging.

Safety recommendations

For more information about safety, see the relevant SABA safety data sheet.