

Periodic Table of The Analytical Fittings

PORT THREAD	3750 PSI 1/16 M-644-03 / M-650 2.3 in-lbs Headless Micro Knurl PEEK	15000 PSI 1/32 UH-904 3.4 in-lbs Headless Knurl PEEK Blend	3750 PSI 1/16 M-660 / M-650 2.3 in-lbs Headless Micro Knurl PEEK	4000 PSI .025 F-125 3.4 in-lbs Standard Micro Knurl PEEK	2500 PSI 1/8 P-331 / P-350 3.4 in-lbs Standard Knurl PEEK TOOL N-290 3.4 in-lbs Micro Headless Knurl	30000 PSI 1/32 VHP-700 20 in-lbs 4 mm Hex SS	25000 PSI 1/32 VHP-920 3 in-lbs 4 mm Hex SS / PEEK Blend	30000 PSI 1/32 VHP-900 / VHP-900-01 20 in-lbs 4 mm Hex SS	5000 PSI 360 µm F-124S 3.4 in-lbs Standard Micro Knurl PEEK	5000 PSI 1/32 F-126S 3.4 in-lbs Standard Micro Knurl PEEK	5000 PSI 1/32 F-126H 3.4 in-lbs Headless Micro Knurl PEEK	5000 PSI 360 µm F-124H 3.4 in-lbs Headless Micro Knurl PEEK	15000 PSI 1/32 PK-126 3.4 in-lbs Standard Micro Knurl PEEK Blend	15000 PSI 1/32 PK-126H 3.4 in-lbs Headless Micro Knurl PEEK Blend	15000 PSI 360 µm PK-124 3.4 in-lbs Standard Micro Knurl PEEK Blend	4000 PSI 1/16 F-100 3.4 in-lbs Diamond Knurl PCTFE	5000 PSI 1/16 F-130 3.4 in-lbs Standard Knurl PEEK	5000 PSI 1/32 F-354 / LT-132 4 in-lbs Flush Nut SS / PEEK	5000 PSI 1/32 LT-110 / LT-132 4 in-lbs Standard Knurl PEEK	6000 PSI 190 µm F-200 / F-148 3.4 in-lbs Single Wing Delrin / PCTFE	6000 PSI 360 µm F-200 / F-151 3.4 in-lbs Single Wing Delrin / PCTFE	6000 PSI 1/32 F-200 / F-113 3.4 in-lbs Single Wing Delrin / PEEK	6000 PSI 1/16 F-200 / F-142 3.4 in-lbs Single Wing Delrin / PEEK	9000 PSI 1/16 F-195 / F-192 4 in-lbs Standard Knurl PEEK	9000 PSI 1/16 F-198 / F-192 4 in-lbs Headless Knurl PEEK	9000 PSI 1/16 F-287 / F-192 4 in-lbs Standard Knurl PEEK / PEEK Blend	11000 PSI 1/16 VHP-3200 3.4 in-lbs Diamond Knurl SS / PEEK Blend	12000 PSI 1/16 PK-120BLK 8 in-lbs Standard Knurl PEEK Blend	20000 PSI 1/16 U-400 / U-401 20 in-lbs 1/4" Hex SS	20000 PSI 1/16 U-420 / U-401 20 in-lbs 1/4" Hex SS	25000 PSI 1/16 VHP-320 10 in-lbs 1/4" Hex SS / PEEK Blend	30000 PSI 1/16 VHP-200 / VHP-200-01 20 in-lbs 1/4" Hex SS	5000 PSI 1/16 F-120 3.4 in-lbs Standard Knurl PEEK	5000 PSI 1/16 F-127 3.4 in-lbs Standard Knurl PEEK	5000 PSI 1/16 F-354 / LT-100 4 in-lbs Flush Nut SS / PEEK	5000 PSI 1/16 LT-110 / LT-100 4 in-lbs Standard Knurl PEEK	6000 PSI 190 µm F-300 / F-148 3.4 in-lbs Double Wing PEEK / PCTFE	6000 PSI 360 µm F-300 / F-151 3.4 in-lbs Double Wing PEEK / PCTFE	6000 PSI 1/32 F-300 / F-113 3.4 in-lbs Double Wing PEEK	6000 PSI 1/16 F-300 / F-142 3.4 in-lbs Double Wing PEEK	9000 PSI 1/16 F-196 / F-192 4 in-lbs Standard Knurl PEEK	9000 PSI 1/16 F-350 / F-192 4 in-lbs Flush Nut SS / PEEK Blend	9000 PSI 1/16 F-284 / F-192 4 in-lbs Headless Knurl PEEK / PEEK Blend	10000 PSI 1/16 LT-110 / LT-135 7 in-lbs Standard Knurl PEEK / PEEK Blend	16500 PSI 1/32 PK-110 / PK-132 8 in-lbs Standard Knurl PEEK Blend	16500 PSI 1/16 PK-110 / PK-100 8 in-lbs Standard Knurl PEEK Blend	20000 PSI 1/16 U-320 / U-321 20 in-lbs 1/4" Hex SS	25000 PSI 1/16 VHP-325 10 in-lbs 1/4" Hex SS / PEEK Blend	30000 PSI 1/16 VHP-205 / VHP-200-01 20 in-lbs 1/4" Hex SS	1000 PSI 1/16 P-249 2.3 in-lbs Standard Knurl PEEK	1000 PSI 1/8 P-349 2.3 in-lbs Standard Knurl PEEK	1000 PSI 1/8 P-331 / P-359 3.4 in-lbs Standard Knurl PEEK / ETFE	1350 PSI 1/16 F-356 / P-259 3.4 in-lbs Flush Nut SS / ETFE	1350 PSI 1/16 P-255 / P-259 3.4 in-lbs Standard Knurl PEEK / ETFE	1500 PSI 1/8 F-156 / P-360 3.4 in-lbs Female Knurl PEEK	1500 PSI 1/8 P-331 / P-360 3.4 in-lbs Standard Knurl PEEK	1850 PSI 1/16 F-356 / P-260 3.4 in-lbs Flush Nut SS / PEEK	1850 PSI 1/16 P-255 / P-260 3.4 in-lbs Standard Knurl PEEK	2500 PSI 1/32 F-356 / P-248 3.4 in-lbs Flush Nut SS / ETFE	2500 PSI 1/32 P-255 / P-248 3.4 in-lbs Standard Knurl PEEK / ETFE	2500 PSI 1/16 F-356 / P-250 3.4 in-lbs Flush Nut SS / PEEK	2500 PSI 1/16 P-255 / P-250 3.4 in-lbs Standard Knurl PEEK	2500 PSI 1/8 F-156 / P-350 3.4 in-lbs Female Knurl PEEK	2500 PSI 1/8 P-331 / P-350 3.4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 F-364 / LT-200 4 in-lbs Flush Nut SS / PEEK	20000 PSI 1/8 C-235 / C-236 40 in-lbs 5/16" Hex SS / PEEK	1000 PSI 1/8 P-100 3.4 in-lbs Standard Knurl PCTFE	1000 PSI 1/8 F-364 / P-359 3.4 in-lbs Flush Nut SS / ETFE	1000 PSI 1/8 P-336 / P-359 3.4 in-lbs Headless Knurl PEEK / ETFE	1350 PSI 1/16 LT-115 / P-259 3.4 in-lbs Standard Knurl PEEK / ETFE	1350 PSI 1/16 P-287 / P-259 3.4 in-lbs Headless Knurl PPS / ETFE	1500 PSI 1/8 P-381 / P-360 3.4 in-lbs Standard Knurl PPS / PEEK	1500 PSI 1/8 F-364 / P-360 3.4 in-lbs Flush Nut SS / PEEK	1500 PSI 1/8 P-336 / P-360 3.4 in-lbs Headless Knurl PEEK	1850 PSI 1/16 LT-115 / P-260 3.4 in-lbs Standard Knurl PEEK	1850 PSI 1/16 P-287 / P-260 3.4 in-lbs Headless Knurl PPS / PEEK	2500 PSI 1/32 LT-115 / P-248 3.4 in-lbs Standard Knurl PEEK / ETFE	2500 PSI 1/32 P-287 / P-248 3.4 in-lbs Headless Knurl PPS / ETFE	2500 PSI 1/16 LT-115 / P-250 3.4 in-lbs Standard Knurl PEEK	2500 PSI 1/16 P-287 / P-250 3.4 in-lbs Headless Knurl PPS / PEEK	2500 PSI 1/8 F-364 / P-350 3.4 in-lbs Flush Nut SS / PEEK	2500 PSI 1/8 P-336 / P-350 3.4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 P-336 / P-350 3.4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 C-235 / LT-200 40 in-lbs 5/16" Hex SS / PEEK	1000 PSI 1/8 F-156 / P-359 3.4 in-lbs Female Knurl PEEK / ETFE	1000 PSI 1/8 LT-215 / P-359 3.4 in-lbs Standard Knurl PEEK / ETFE	1000 PSI 1/8 P-387 / P-359 3.4 in-lbs Headless Knurl PPS / ETFE	1350 PSI 1/16 P-232 / P-259 3.4 in-lbs Headless Knurl PEEK / ETFE	1350 PSI 1/16 P-420 / P-259 3.4 in-lbs Standard Knurl PEEK / ETFE	1500 PSI 1/8 LT-215 / P-360 3.4 in-lbs Standard Knurl PEEK	1500 PSI 1/8 P-387 / P-360 3.4 in-lbs Headless Knurl PPS / PEEK	1850 PSI 1/16 P-232 / P-260 3.4 in-lbs Headless Knurl PEEK	1850 PSI 1/16 P-420 / P-260 3.4 in-lbs Female Knurl PEEK	2500 PSI 1/32 P-232 / P-248 3.4 in-lbs Headless Knurl PEEK / ETFE	2500 PSI 1/32 P-420 / P-248 3.4 in-lbs Female Knurl PEEK / ETFE	2500 PSI 1/16 P-232 / P-250 3.4 in-lbs Headless Knurl PEEK	2500 PSI 1/16 P-420 / P-250 3.4 in-lbs Female Knurl PEEK	2500 PSI 1/8 LT-215 / P-350 3.4 in-lbs Standard Knurl PEEK	2500 PSI 1/8 P-387 / P-350 3.4 in-lbs Standard Knurl PPS / PEEK	4500 PSI 1/8 LT-215 / LT-200 4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 LT-210 / LT-200 4 in-lbs Double Wing PEEK	1000 PSI 1/16 P-229 2.3 in-lbs Standard Knurl PEEK	1000 PSI 1/8 P-329 2.3 in-lbs Standard Knurl PEEK	1000 PSI 2.5 mm P-317 / P-366 3.4 in-lbs Standard Knurl PEEK	1350 PSI 1/16 P-213 / P-259 3.4 in-lbs Headless Knurl PEEK / ETFE	1350 PSI 1/16 P-219 / P-259 3.4 in-lbs Standard Knurl PEEK / ETFE	1350 PSI 1/16 P-217 / P-259 3.4 in-lbs Standard Knurl PEEK / ETFE	2500 PSI 1/32 P-213 / P-248 3.4 in-lbs Headless Knurl PEEK / ETFE	2500 PSI 1/32 P-219 / P-248 3.4 in-lbs Standard Knurl PEEK	2500 PSI 1/16 P-213 / P-250 3.4 in-lbs Headless Knurl PEEK	2500 PSI 1/8 P-219 / P-250 3.4 in-lbs Standard Knurl PEEK	2500 PSI 1/8 P-317 / P-352 3.4 in-lbs Standard Knurl PPS / PEEK	2500 PSI 1/8 P-319 / P-352 3.4 in-lbs Standard Knurl PEEK	2500 PSI 1.8 mm P-317 / P-355 3.4 in-lbs Standard Knurl PPS / PCTFE	2500 PSI 1.8 mm P-319 / P-355 3.4 in-lbs Standard Knurl PEEK / PCTFE	5000 PSI 2.0 mm P-357 / P-357-2 3.4 in-lbs Standard Knurl PEEK	9000 PSI 1/16 F-197 / F-192 4 in-lbs Standard Knurl PEEK	20000 PSI 1/16 U-450 / U-401 20 in-lbs 5/16" Hex SS
-------------	---	--	--	--	--	--	--	---	---	---	---	---	--	---	--	--	--	---	--	---	---	--	--	--	--	---	--	---	--	--	---	---	--	--	---	--	---	---	---	---	--	--	---	--	---	---	--	---	---	--	---	--	--	---	---	---	--	--	--	---	--	--	---	---	--	---	--	---	--	--	--	---	---	---	---	--	--	--	---	--	---	---	---	---	--	---	---	---	---	--	---	--	--	---	---	--	--	--	---	---	--	--	---	--	---	---	---	---	--	--	---	---	---	---	--	--	--	---

For more information, please visit www.biotech.se, or contact your local Biotech office:

Global Headquarters
Biotech AB
www.biotech.se
info@biotech.se
+46 (0) 300 569180

North America
Biotech USA LLC
www.biotech.se
bmathieu@biotechusa.us
+1 (0) 612 703 5718

Japan
BioNik Inc
www.bionikinc.com
info@bionikinc.com
+81 (0) 545 38 9125

LEGEND

1 Pressure Rating
2 Tubing Size
3 Fitting / Ferrule Part Number
4 Torque Required
5 Head Style
6 Fitting / Ferrule Material

TOOL

7 Tool Category
8 Tool Part Number
9 Torque Required
10 Head Style

ICONS

Tool Required

HAND TIGHTENING/EXTENDER TOOLS								PRE-SET TORQUE TOOLS				
F-345 3.4 in-lbs Flush Nut-10-32	F-346 3.4 in-lbs Flush Nut 1/4-28	N-290 3.4 in-lbs Micro Headless Knurl	P-277 3.4 in-lbs Standard Micro Knurl	P-297 3.4 in-lbs Headless Knurl	P-299 3.4 in-lbs Standard Knurl	P-399 3.4 in-lbs Standard Micro Knurl	VHP-1001 10 in-lbs 1/4" Hex	VHP-9000 2-10 in-lbs 4 mm Hex	VHP-1000 10 in-lbs 1/4" Hex	VHP-2000 14 in-lbs 1/4" Hex	VHP-3000 10 in-lbs 8 mm Hex	P-1000 4 in-lbs Standard Knurl

ADJUSTABLE TORQUE DRIVER AND TORQUE DRIVER EXTENDER TOOLS						
VHP-4000 2-10 in-lbs 1/4" Drive	N-291 2-10 in-lbs Micro Headless Knurl	P-268 2-10 in-lbs 1/4" Hex	P-278 2-10 in-lbs Female Nut Knurl	P-279 2-10 in-lbs Micro Knurl	P-291 2-10 in-lbs Standard Knurl	F-347 2-10 in-lbs Flush Nut 1/4-28



Innovations United
300 East 57th Street Suite 11J
New York, NY 10022
Web: www.innovationsunited.com
Tel: 212-204-0075
Fax: 484-313-6368
Email: info@innovationsunited.com

Copyright © 2015 DEK Health & Science LLC. DEK Health & Science LLC is a Unit of IDEC Corporation. | ID0115