



Innospray B600

Safety Data Sheet

SECTION 1: Identification

1.1. Identification

Product name : Innospray B600

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Ready-to-use spray cleaner with alcohol, for use according to the user instructions.

1.3. Details of the supplier of the safety data sheet

Zahav LLC dba Clean My Steel
20423 State Rd. 7
Boca Raton, FL 33498

1.4. Emergency telephone number

Emergency number : 561-410-3636

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Liq. 3 H226

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS02

Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethyl alcohol	(CAS-No.) 64-17-5	15 – 20	Flam. Liq. 2, H225 Carc. 1A, H350
Propylene glycol monomethyl ether	(CAS-No.) 107-98-2	1 – 5	Flam. Liq. 3, H226

Innospray B600

Safety Data Sheet

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Provide fresh air.
- First-aid measures after skin contact : After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.
- First-aid measures after eye contact : Rinse immediately carefully and thoroughly with eye-bath or water.
- First-aid measures after ingestion : Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water jet, alcohol-resistant foam, carbon dioxide, extinguishing powder.
- Unsuitable extinguishing media : Full water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapor.
- Explosion hazard : None known.
- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with eyes, skin and clothing.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : If possible, stop flow of product.
- Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal .

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with eyes, skin and clothing. Do not mix with other chemicals. Wear personal protection equipment (see chapter 8). When using do not eat, drink or smoke. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep away from ignition sources. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethyl alcohol (64-17-5)

ACGIH	ACGIH STEL (ppm)	1000 ppm
-------	------------------	----------

Innospray B600

Safety Data Sheet

Ethyl alcohol (64-17-5)		
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
Propylene glycol monomethyl ether (107-98-2)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	360 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	540 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm

8.2. Exposure controls

Appropriate engineering controls	: General (mechanical) room ventilation is expected to be satisfactory for normal handling.
Hand protection	: Nitrile rubber gloves.
Eye protection	: None required under normal product handling conditions.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Transparent
Odor	: Fragrant
Odor threshold	: No data available
pH	: 9.8 – 10.8
Melting point	: -5 °C
Freezing point	: No data available
Boiling point	: > 85 °C
Flash point	: 36 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.97 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: < 10 mPa·s
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

Innospray B600

Safety Data Sheet

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

Not determined.

10.6. Hazardous decomposition products

Oxides of carbon may be formed during combustion.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg
LC50 inhalation rat (mg/l)	124.7 mg/l/4h
ATE US (oral)	7060 mg/kg

Propylene glycol monomethyl ether (107-98-2)	
LD50 oral rat	5000 mg/kg
LD50 dermal rabbit	13 g/kg
LC50 inhalation rat (ppm)	> 7559 ppm (Exposure time: 6 h)
ATE US (oral)	5200 mg/kg body weight
ATE US (dermal)	13000000 mg/kg body weight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ethyl alcohol (64-17-5)	
LC50 fish 1	12.0 – 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Innospray B600

Safety Data Sheet

Propylene glycol monomethyl ether (107-98-2)

LC50 fish 1	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethyl alcohol (64-17-5)

Partition coefficient n-octanol/water (Log Pow)	-0.32
---	-------

Propylene glycol monomethyl ether (107-98-2)

BCF fish 1	< 2
Partition coefficient n-octanol/water (Log Pow)	-0.437

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (Ethyl Alcohol), 3, III

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
Ethyl Alcohol

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

Innospray B600

Safety Data Sheet

DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

Ethyl alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Propylene glycol monomethyl ether (107-98-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Ethyl alcohol (64-17-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	No	

Ethyl alcohol (64-17-5)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Propylene glycol monomethyl ether (107-98-2)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Innospray B600

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases:

Carc. 1A	Carcinogenicity Category 1A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H350	May cause cancer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.