

# Acrylic Gesso for Artists

---

## Product Description

Designed for canvas but compatible with wood, paper, metal, masonry- any surface that can accept acrylic media. Featherweight and non-toxic, tintable and non-yellowing, Breathing Color's Acrylic Gesso is the right viscosity for singular results in a single coat.




---

## Physical Specifications

Carrier	Water
Pigment Identification	PW6
Lightfastness	Testing in progress
Permanency	Excellent
Opacity	1 (1=most opaque and 8=most transparent)
Viscosity	2,500-3,500 cPs (as measured on a Brookfield viscometer)
pH	8.0-9.0




---

## Key Features

**Flexibility:** Adequate flexibility to withstand loose rolling and re-stretching at room temperature. Paint films become more brittle below 50°F, and should not be bent, stretched or flexed under such conditions. Withstands expansion and contraction caused by changes in temperature and humidity.

**Drying/Curing Time:** A 5 mils wet film will dry to touch within 1 hours when temperature is above 65°F and humidity is below 70%. Lower temperatures and/or higher humidity can slow the drying process considerably.

**Other:**

- Apply and dry in minutes for artwork that is stable and vibrant
- The perfect viscosity to use right out of the bottle
- Add water resistance to any substrate

---

## Additional Information

Storage	70°F (21°C) / 50% Relative Humidity; store in original packaging and in a controlled environment
Shelf Life	Minimum 1 year from purchase date, when stored as specified
Lamination	Not required

**Note:** Actual stability will vary according to media, all mediums used, application method and amount, display conditions, light intensity, and atmospheric conditions. Breathing Color does not guarantee the longevity of artwork. For maximum display life, all artwork should be properly displayed or stored. All of the descriptive information and recommendations for the use of Breathing Color products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by Breathing Color. All purchasers of Breathing Color products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss of damage, direct, incidental, or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.