

# Photo Peel Always Gloss

## Product Description

We took the same high-quality, non-glare PVC film used in Photo Peel and upgraded the pressure sensitive adhesive backing for permanent fixing. Cold laminate for industry leading durability and excellent color brilliance.



## Physical Specifications

Base Composition	PVC Vinyl
Basis Weight	310 gsm (with liner)
Caliper	8.5 mils (without liner)
Opacity	95%
Gloss	50 GU
CIE L*a*b* (F7/2)	L*94.0 / a* 0.5 / b* (-5.7)
Texture	Smooth
Finish	Gloss
Core Diameter	2"



## Printer Compatibility & Handling

**Aqueous Piezo Printer Compatibility** . . . . . Epson®, Roland®  
Mutoh®, Mimaki®

**Aqueous Thermal Printer Compatibility** . . . . . Canon®, HP®  
ColorSpan®, Encad Novajet®

**Solvent Printer Compatibility** . . . . . N/A

**Ink Compatibility** . . . . . All Dyes & Pigments

**Optimal Print Environment** . . . . . 70°F (21°C), 30-60% Relative Humidity

**Handling:** Avoid touching the coated surface. Cotton gloves should be used when handling inkjet coated materials from Breathing Color.

**Note:** Coated surface of every roll faces out.

## Additional Information

**Storage** . . . . . 70°F (21°C) / 50% Relative Humidity; store in original packaging and in a controlled environment

**Shelf Life** . . . . . Minimum 1 year from purchase date, when stored as specified

**Lamination** . . . . . Not required

**Print Settings & ICC Profiles** . . . . . Custom ICC Profile will produce optimum results

**Note:** Actual print stability will vary according to media, printed image, display conditions, light intensity and atmospheric conditions. Breathing Color does not guarantee the longevity of prints. For maximum print life display all prints under glass or lamination or properly store them. All of the descriptive information and recommendations for the use of Breathing Color products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by Breathing Color. All purchasers of Breathing Color products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss of damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.