
Radiance™ Transfer Paper

Product Description

For quick drying, rapid transfers on a variety of substrates, Radiance Transfer Paper performs with aplomb. Breathing Color's renowned HD print quality ensures crack and fade resistant pressings never looked so vibrant.



Physical Specifications

Basis Weight
Caliper
Opacity
Gloss
Whiteness
Core Diameter

Printer Compatibility & Handling

Aqueous Piezo Printer Compatibility
Aqueous Thermal Printer Compatibility
Solvent Printer Compatibility
Ink Compatibility
Optimal Print Environment 70°F (21°C), 30-60% Relative Humidit

Handling: Avoid touching the coated surface. Cotton gloves should be used when handling inkjet coated materials from Breathing Color.

Note: Coated surface of every roll faces out.

Additional Information

Storage	70°F (21°C) / 50% Relative Humidity; store in original packaging and in a controlled environment
Shelf Life	Minimum 1 year from purchase date, when stored as specified
Lamination	Not required
Print Settings & ICC Profiles	

Note: Actual print stability will vary according to media, printed image, display conditions, light intensity and atmospheric conditions. Breathing Color does not guarantee the longevity of prints. For maximum print life display all prints under glass or lamination or properly store them. All of the descriptive information and recommendations for the use of Breathing Color products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by Breathing Color. All purchasers of Breathing Color products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss of damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.

