

Vibrance Metallic

Product Description

Vibrance Metallic’s pearlescent finish is breathtaking in large format displays and when face mounted to acrylic. Industry leading saturations on a resin coated, blended base, Vibrance Metallic handles high ink loads without bleeding or cockling.



Physical Specifications

Base Composition	Resin Coated Cellulose Blend
Basis Weight	255 gsm
Caliper	10 mils
Opacity	96%
Gloss	50 GU
CIE L*a*b* (F7/2)	L*93.8 / a* 3.9 / b* (-7.3)
Texture	Ultra Smooth
Finish	Pearlescent
Core Diameter	3"

Printer Compatibility & Handling

Aqueous Piezo Printer Compatibility Epson®, Roland®
Mutoh®, Mimaki®

Aqueous Thermal Printer Compatibility Canon®, HP®
ColorSpan®, Encad Novajet®

Solvent Printer Compatibility N/A

Ink Compatibility All Dyes & Pigments

Optimal Print Environment 70°F (21°C), 30-60% Relative Humidity

Handling: Avoid touching the coated surface. Cotton gloves should be used when handling inkjet coated materials from Breathing Color.

Note: Coated surface of every roll faces out.

Additional Information

Storage 70°F (21°C) / 50% Relative Humidity; store in original packaging and in a controlled environment

Shelf Life Minimum 1 year from purchase date, when stored as specified

Lamination Not required

Print Settings & ICC Profiles Custom ICC Profile will produce optimum results

Note: Actual print stability will vary according to media, printed image, display conditions, light intensity and atmospheric conditions. Breathing Color does not guarantee the longevity of prints. For maximum print life display all prints under glass or lamination or properly store them. All of the descriptive information and recommendations for the use of Breathing Color products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by Breathing Color. All purchasers of Breathing Color products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller’s and manufacturer’s only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss of damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.