

BIG BEAVER SPECIFICATIONS

		BIG BEAVER
CONSTRUCTION	FRAME	We Rent the BIG BEAVER XL machine
	MAST	
	DRILLING ANGLE	
	STABILIZER	
HYDRAULICS	AUGER SPEED @ 10 GPM*	
	AUGER SPEED @ 12 GPM*	
	DRILLING TORQUE*	
	MAX. DRILLING TORQUE	
	RAISING CAPACITY	
	HYDRAULIC VALVES	
	DRIVE HEAD TRAVEL	
	MAXIMUM AUGER SIZE	
MAXIMUM AUGER LENGTH		
DIMENSIONS	HEIGHT	
	LENGTH	
	WIDTH	
	SHIPPING WEIGHT	

BIG BEAVER XL

Welded Mechanical Steel Tubing
1.5-inch Diameter Drive Screw and Structural Steel Angle
Infinitely Adjustable 0-15° From Vertical
Torque Tube
160 rpm
190 rpm
520 ft lbs*
690 ft lbs*
2500 lbs
2
72 inches
18 inches
Up to 5 feet long
92 inches
48 inches
26 inches
730 lbs

HYDRAULIC POWER SOURCE SPECIFICATIONS

		PS-20HC
ENGINE	BRAND / MODEL	Honda GX630
	POWER @ 3600 RPM	20.8 hp net
	FUEL TANK CAPACITY	5 US gal
	STARTING	Electric
	COOLING	Air
HYDRAULICS	MAXIMUM FLOW	10 gpm
	HYDRAULIC PRESSURE	1500 to 3000 psi
	RESERVOIR CAPACITY	5 US gal
	OIL COOLER W/ FAN	Standard
	HOURLY METER	Standard
	FORWARD / REVERSE	Standard
	RETURN FILTER	10 micron
	INLET SUCTION STRAINER	100 US mesh
OIL LEVEL INDICATOR	Dipstick	
SIZE WITH WHEEL KIT	LENGTH	54 in
	WIDTH	30 in
	HEIGHT	30 in
	DRY WEIGHT	310 lbs
SIZE WITHOUT WHEEL KIT	LENGTH	40 in
	WIDTH	25 in
	HEIGHT	25 in
	DRY WEIGHT	275 lbs

And the PS-20HC is part of the package