

Warranty Information

Proof of purchase will be required.

The guarantee does not cover faults or damage caused by incorrect installation and/or maintenance, ordinary wear and tear, water composition, etc.

*Please see www.deva-uk.com for full terms and conditions of warranty

Cleaning

Your product has a high-quality finish and should be treated with care to preserve the visible surfaces. Never use abrasives or abrasive cleaning agents to clean this product clean regularly with contamination free warm water and a damp soft cloth. Do not use products containing chlorine bleach or hydrochloric acid as these can damage the product.

We have a policy of continuous improvement and reserve the right to change specifications without notice.

METHVEN UK LIMITED
METHVEN EXPERIENCE CENTRE
3/3A STONE CROSS COURT
YEW TREE WAY
GOLBORNE
WARRINGTON
WA3 3JD
UNITED KINGDOM
INST-ARMCO4
18/08/2022

TEL: 0800 195 1602
FAX: 0844 406 8690
EMAIL: sales@uk.methven.com
www.methven.com
www.deva-uk.com

Ceiling Mounted Shower Arm

ARMCO4

Installation Guide

Technical Specification

Operating Pressure

Min: 0.1 Bar

Max: 5.0 Bar

Operating Temperature

Hot: 65°C

Cold: 5°C

Inlet Connections

1/2" BSP

Features:

- Sleek Contemporary Design
- Brass Construction
- Pair with a round or square shower head



Congratulations on your purchase of your new Deva by Methven Shower Arm. Our fitting instructions have been created with you in mind to provide you with all the information you require and, if you need any further help, please don't hesitate to contact our customer care team on 0800 195 1602.

Please read all of the instructions before installation.

General

Methven recommends this product is installed by a competent person in compliance with all relevant regional regulations.

Remove all packaging and check the components for damage before starting installation.

This product must not be modified in any way as this will invalidate the guarantee.

It is the responsibility of the installer to ensure a waterproof seal is achieved, after installation all connections must be checked for leaks. All outlets used primarily for personal hygiene shall deliver water at a safe temperature as per regional regulations.

Installation Instructions

Before commencing installation of the new product, ensure that the system has been flushed to remove any debris, which could cause damage and invalidate the warranty.

1. Install a ½" male threaded connection at the desired position on the ceiling.
2. Slide trim ring onto the appropriate end of the arm.
3. Screw the arm onto the ½" connection using plumbers tape (NOT SUPPLIED) or similar to ensure a reliable seal.
4. Push trim ring into place.
5. Connect the shower head (NOT SUPPLIED) to the shower arm thread and screw on until the head is secured in position (DO NOT OVERTIGHTEN)
6. Tilt and rotate the shower head to the desired position.
7. Reinstate the water supply and check for any leaks.