


TECKEL

Studio Eurolinea Design, 2016



COLLECTION

www.interracontract.com
info@interracontract.com
O: 949.497.0277



0,38 m³ - 22 kg
59x65x99cm
4 pcs [carton]

Stackable on floor [4pcs]

Painted 4-legged frame, mesh back.

PERFORMED TEST

1. Safety requirements EN 16139:2013+AC:2013
2. Information for use EN 16139:2013+AC:2013
3. Seat and back static load test EN 1728:2012+AC:2013
4. Vertical load on back rest EN 1728:2012+AC:2013
5. Seat and back fatigue test EN 1728:2012+AC:2013
6. Seat front edge durability test EN 1728:2012+AC:2013
7. Leg forward static load test EN 1728:2012+AC:2013
8. Leg sideways static load test EN 1728:2012+AC:2013
9. Seat impact test EN 1728:2012+AC:2013
10. Back impact test EN 1728:2012+AC:2013
11. Stability - EN 1022:2005




FRAME FINISHES



CUSHION
Upholstered cushion.



MESH
Available colors for mesh back.



CUSHION AVAILABLE FABRICS

- [B] Blazer Fabric
- [DK] Kvadrat Fabric - Steelcut 2
- [DK] Kvadrat Fabric - Remix 2
- [K] King Fabric
- [L] King L Fabric

[TC] COM Fabric
Cushion fabric required 2pcs: Lin Mtrs 0,6 (h 1,40)


FIRE RETARDANT

Products follows UNI 9175 -UNI 9175/FA, in terms of Fire Resistance, Fire Reation Class 1IM.



ACCESSORIES

TROLLEY
Painted grey adjustable dolly, for 4 legged chairs.



QUALITY IN THE NATURAL RESPECT

100% Demountable product
100% Recyclable material
100% Made in Italy

TECHNOPOLYMER

Gaber production employs exclusively high-tech thermoplastic materials, which are 100% recyclable. Gaber produces plastic injected materials without added chemicals. These materials are purchased within the European Union, so Gaber is exempted from registration with ECHA agency (European Agency for Chemicals Substances), in the complete respect of "Reach Regulation".

METAL

Gaber metal structures, in the full respect of our Natural Environment, are available with "trivalent" chroming and painted finishes. Prime-quality special Epoxy powder coating used on Gaber frames enhance color stability from batch to batch and over time, increasing its corrosion-resistance and achieving excellent resistance to atmospheric agents.

PADDINGS

The flexible polyurethane cold-pressed paddings Gaber uses on its upholstered articles do not contain CFC/HCFC (ODP=0: do not contribute the reduction of the atmospheric ozone layer), they are fire-retardant class 1-IM UNI 9175/CMHR following European Standards.

CARTON BOXES

Corrugated paperboard carton boxes, printed with environmentally friendly inks, are made of 90% recycled and recyclable materials. Packaging is sized in order to optimize storage and transport requirements, both helping the environment and saving on transport costs.

In all components, parts or materials used by Gaber to make its own products, be they plastic or metal, there are no dangerous substances within the certified limits of the following test methods reports:

Cadmium UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Lead UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Mercury UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Arsenic UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Selenium UNI EN 13656:2004 + UNI EN 13657:2004 + UNI EN ISO 11885:2009
Chrome VI CEI EN 62321:2009 Annex C
Diisobutil ftalato (DIBP) CPSC-CH-C1001-09.3:2010
Dibutil ftalato (DBP) CPSC-CH-C1001-09.3:2010
Benzilbutil ftalato (BBP) CPSC-CH-C1001-09.3:2010
Di-(2-etilesil) ftalato (DEHP) CPSC-CH-C1001-09.3:2010

Di-n-ottil ftalato (DNOP) CPSC-CH-C1001-09.3:2010
Diisononil ftalato (DINP) CPSC-CH-C1001-09.3:2010
Diisodecil ftalato (DIDP) CPSC-CH-C1001-09.3:2010
Dipentil ftalato (DPP) CPSC-CH-C1001-09.3:2010
Dimetossietil ftalato (DMEP) CPSC-CH-C1001-09.3:2010

Gaber Material "Plastomero" Report n. 20205954-002
Gaber Material "Polipropilene" Report n. 20205139-002
Gaber Material "Metal tube" Report n. 20205954-001



TECKEL COLLECTION

Considerable research at stylistic and ergonomic levels sums up this stylishly comfortable chair. The handle in the backrest makes for easy manoeuvrability.

